



### Main

Range of product	Zelio Relay
Series name	Miniature
Status LED	Without
Control type	Pushbutton
Control circuit voltage	24 V DC
Contacts type and composition	4 C/O
Contacts operation	Standard
Coil interference suppression	Without
[the] conventional enclosed thermal current	6 A ≤ 55 °C
Load current	6 A 250 V AC 6 A 28 V DC
Utilisation coefficient	20 %
Sale per indivisible quantity	10

### Complementary

[Ui] rated insulation voltage	250 V IEC 300 V UL 300 V CSA
[Uimp] rated impulse withstand voltage	4 kV IEC 61000-4-5
Contacts material	Silver alloy (Ag/Ni)
[Ie] rated operational current	3 A NC AC-1/DC-1 IEC 6 A NO AC-1/DC-1 IEC 8 A AC-1/DC-1 UL
Minimum switching current	10 mA
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	17 V
Maximum switching capacity	168 W DC 1500 VA AC
Minimum switching capacity	170 mW
Operating rate	≤ 20 cyc/mn under load ≤ 300 cyc/mn no-load
Mechanical durability	10000000 cycles
Electrical durability	100000 cycles resistive
Average consumption in W	0,9 W DC
Average consumption in VA	1,2 AC
Drop-out voltage threshold	≥ 0.15 Uc AC ≥ 0.1 Uc DC
Operating time	20 ms between coil de-energisation and making of the Off-delay contact AC/DC 20 ms between coil energisation and making of the On-delay contact AC/DC
Average resistance	650 Ohm DC 20 °C +/- 10 %
Rated operational voltage limits	19.2...26.4 V DC
Protection category	RT I
Operating position	Any position
Product weight	0,037 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Dielectric strength	1500 V AC between contacts 1550 V AC between coil and contact 1550 V AC between poles
Product certifications	CSA UL
Standards	CSA C22-2 No 14 EN/IEC 61810-1 (iss. 2) UL 508
Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-40...55 °C
Vibration resistance	3 gn +/- 1 mm 10...150 Hz opening EN/IEC 60068-2-27 5 gn +/- 1 mm 10...150 Hz closing EN/IEC 60068-2-27
IP degree of protection	IP40 EN/IEC 60529
Shock resistance	15 gn closing EN/IEC 60068-2-27 15 gn opening EN/IEC 60068-2-27
RoHS EUR conformity date	0801
RoHS EUR status	Compliant