ZB4BA26

round head for pushbutton Ø 22 - spring return - recessed - black - unmarked



Main Range of product Harmony XB4 Product or component Head for pushbutton type ZB4 Device short name Bezel material Chromium plated metal Mounting diameter 22 mm Sale per indivisible 1 quantity IP66 IEC 60529 IP degree of protection Shape of signaling unit Round head Type of operator Spring return Operator profile Recessed black unmarked Operator additional in-High guard formation

Complementary

Resistance to high pressure washer	7000000 Pa 55 °C 0.1 m
Mechanical durability	5000000 cycles

Environment		
Protective treatment	TH	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-2570 °C	
Class of protection against electric shock	Class I IEC 60536	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK03 IEC 50102	
Standards	CSA C22-2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508	
Product certifications	BV CSA DNV (Det Norske Veritas) GL LROS (Lloyds register of shipping) RINA UL listed	
Vibration resistance	5 gn 2500 Hz IEC 60068-2-6	
Shock resistance	30 gn 18 ms half sine wave acceleration IEC 60068-2-27 50 gn 11 ms half sine wave acceleration IEC 60068-2-27	
RoHS EUR conformity date	0727	
RoHS EUR status	Compliant	