



Main

| | |
|-------------------------------|-----------------------|
| Range of product | Harmony XB4 |
| Product or component type | Head for pushbutton |
| Device short name | ZB4 |
| Bezel material | Chromium plated metal |
| Mounting diameter | 22 mm |
| Sale per indivisible quantity | 1 |
| IP degree of protection | IP66 IEC 60529 |
| Shape of signaling unit head | Round |
| Type of operator | Spring return |
| Operator profile | Flush red O white |

Complementary

| | |
|------------------------------------|------------------------|
| Resistance to high pressure washer | 7000000 Pa 55 °C 0.1 m |
| Mechanical durability | 5000000 cycles |

Environment

| | |
|--|---|
| Protective treatment | TH |
| Ambient air temperature for storage | -40...70 °C |
| Ambient air temperature for operation | -25...70 °C |
| Class of protection against electric shock | Class I IEC 60536 |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| IK degree of protection | IK03 IEC 50102 |
| Standards | CSA C22-2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 |
| Product certifications | BV CSA DNV (Det Norske Veritas) GL LROS (Lloyds register of shipping) RINA UL listed |
| Vibration resistance | 5 gn 2...500 Hz IEC 60068-2-6 |
| Shock resistance | 30 gn 18 ms half sine wave acceleration IEC 60068-2-27 50 gn 11 ms half sine wave acceleration IEC 60068-2-27 |
| RoHS EUR conformity date | 0646 |
| RoHS EUR status | Compliant |