



Main

| | |
|---------------------------|------------------------|
| Product or component type | Starter |
| Type | S |
| Control Circuit Type | Common control circuit |

Complementary

| | |
|-------------------------|----------------------------------------------------------------------|
| Control Circuit Voltage | 220 V AC 50 Hz 240 V AC 60 Hz |
| Motor starter type | Non reversing |
| Line Rated Current | 9 A |
| Number of Poles | 3P |
| Phase | 3 phases |
| Horsepower Rating | 1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 575 V AC |
| System Voltage | 600 V AC |
| Control Units | No control units |
| Thermal overload type | Melting alloy 3 Thermal Units |
| Electrical connection | Screw clamp terminals |
| NEMA size | 00 |
| Height | 10 in (254 mm) |
| Depth | 5.55 in (141 mm) |
| Width | 5.98 in (152 mm) |

Environment

| | |
|------------------------|----------------------------|
| Enclosure Type | NEMA 1 painted sheet steel |
| Product certifications | CSA NEMA UL listed |

Offer Sustainability

| | |
|------------------------|-----------------------|
| RoHS (date code: YYWW) | Will not be compliant |
| | Will not be compliant |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
