



Main

| | |
|---------------------------|------------------------|
| Product or component type | Starter |
| Type | S |
| Control Circuit Type | Common control circuit |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 440 V AC 50 Hz 480 V AC 60 Hz |
| Motor starter type | Non reversing |
| Line Rated Current | 27 A |
| Number of Poles | 3P |
| Phase | 3 phases |
| Horsepower Rating | 7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC |
| System Voltage | 600 V AC |
| Control Units | No control units |
| Thermal overload type | Melting alloy 3 Thermal Units |
| Electrical connection | Screw clamp terminals |
| NEMA size | 1 |
| Height | 12.76 in (324 mm) |
| Depth | 8.54 in (217 mm) |
| Width | 6.38 in (162 mm) |

Environment

| | |
|------------------------|-----------------------------|
| Enclosure Type | NEMA 12 painted sheet steel |
| Product certifications | CSA NEMA UL listed |

Offer Sustainability

| | |
|------------------------|-----------------------|
| RoHS (date code: YYWW) | Will not be compliant |
| | Will not be compliant |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
