



Main

| | |
|---------------------------|------------------------|
| Product or component type | Starter |
| Type | S |
| Control Circuit Type | Common control circuit |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 220 V AC 50 Hz 240 V AC 60 Hz |
| Motor starter type | Non reversing |
| Line Rated Current | 45 A |
| Number of Poles | 3P |
| Phase | 3 phases |
| Horsepower Rating | 10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC |
| System Voltage | 600 V AC |
| Control Units | No control units |
| Thermal overload type | Melting alloy 3 Thermal Units |
| Electrical connection | Screw clamp terminals |
| NEMA size | 2 |
| Height | 7.8 in (198 mm) |
| Depth | 4.92 in (125 mm) |
| Width | 4.29 in (109 mm) |

Environment

| | |
|------------------------|--------------------------|
| Enclosure Type | Not rated (open device) |
| Product certifications | CSA NEMA UL listed |

Offer Sustainability

| | |
|------------------------|-----------------------|
| RoHS (date code: YYWW) | Will not be compliant |
| | Will not be compliant |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
