



### Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Product or component type | Electrically Held Lighting Contactor |
| Range of product          | 8903L                                |
| Control Circuit           | Separate control circuit             |

### Complementary

|                         |                                   |
|-------------------------|-----------------------------------|
| Control Circuit Voltage | 24 V AC 60 Hz                     |
| Current Rating          | 20 A tungsten<br>30 A fluorescent |
| Number of Poles         | 6P 6 NO                           |
| Control Unit            | No control units                  |
| Pilot Light             | No indicator                      |
| Electrical connection   | Screw-clamp terminals             |

### Environment

|                        |   |
|------------------------|---|
| Enclosure Type         | NEMA 1 painted sheet steel and with surface Mounting; |
| Product certifications | CSA<br>UL listed                                      |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| RoHS (date code: YYWW)           | Compliant - since 1431 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications