



### Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Product or component type | Mechanically Held Lighting Contactor |
| Range of product          | 8903LX                               |
| Control Circuit           | Separate control circuit             |

### Complementary

|                       |                                   |
|-----------------------|-----------------------------------|
| Control Voltage       | 110 V AC 50 Hz<br>120 V AC 60 Hz  |
| Current Rating        | 20 A tungsten<br>30 A fluorescent |
| Number of Poles       | 2P 2 NO                           |
| Control Unit          | No control units                  |
| Pilot Light           | No indicator                      |
| Electrical connection | Screw-clamp terminals             |

### Environment

|                        |   |
|------------------------|---|
| Enclosure Type         | Painted sheet steel NEMA 1 and with surface Mounting; |
| Product certifications | CSA<br>UL listed                                      |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| RoHS (date code: YYWW)           | Compliant - since 1431 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|