9001SKP1G31 PILOT LIGHT 120VAC 30MM SK +OPTIONS



Product or component type	Pilot light
Lens type	Fresnel plastic
Light block supply	Via transformer (f = 50/60 Hz) Via integral transformer (f = 50/60 Hz)

Complementary

Product or component type	Pilot light		
Lens type	Fresnel plastic Via transformer (f = 50/60 Hz) Via integral transformer (f = 50/60 Hz)		
Light block supply			
Complementary			
Bezel material	Plastic		
Mounting diameter	30 mm		
Shape of signaling unit head	Round		
Cap/Operator or lens colour	Green		
Light source	Incandescent		
Bulb base	BA 9s		
[Us] rated supply voltage	110120 V AC		
Operating position	Any position		
Operating mode	Normal		
CAD overall width	54 mm		
CAD overall height	70 mm		
CAD overall depth	42 mm		
Device presentation	Complete product		
Environment			
Protective treatment	TC		
IP degree of protection	IP66		
Offer Sustainability			
RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity		
•	Schneider Electric declaration of conformity		
REACh	Reference not containing SVHC above the threshold		
	Reference not containing SVHC above the threshold		

Environment

Protective treatment	TC	
IP degree of protection	IP66	

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	i
REACh	Reference not containing SVHC above the threshold	— E
	Reference not containing SVHC above the threshold	This A