



Main

| | |
|---------------------|----------------------------|
| Product | Single Unit Manual Starter |
| Type | F |
| Overload Relay Type | Melting alloy |

Complementary

| | |
|-----------------------|--|
| Line Rated Current | 16 A |
| Cable entry | Without |
| Horsepower Rating | 1 hp at 115 V AC 1 hp at 230 V AC 1 hp at 277 V AC |
| System Voltage | 277 V AC |
| Number of Poles | 1P |
| Control Unit | Toggle switch |
| Phase | 1 phase |
| Pilot Light | Red indicator |
| Reset | Manual |
| Motor starter type | Non reversing |
| Electrical connection | Screw clamp terminals |
| Wire Gauge | AWG 14...AWG 12 (copper) |
| Height | 4.13 in |
| Width | 1.69 in |
| Depth | 2.22 in |

Environment

| | |
|------------------------|---|
| Product certifications | CSA LR25490 class 3211 05 UL recognized E42243 CCN NLRV2 |
| NEMA Enclosure Rating | Not rated (open device) |

Offer Sustainability

| | |
|------------------------|-----------------------|
| RoHS (date code: YYWW) | Will not be compliant |
| | Will not be compliant |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
