



### Main

Product	Single Unit Manual Switch
Type	K

### Complementary

Line Rated Current	30 A
Cable Entry	0.5" and 0.75" knock-outs (top and bottom)
Horsepower Rating	2 hp at 115 V AC 1 hp at 90 V DC 2 hp at 115 V DC 1.5 hp at 230 V DC 7.5 hp at 230 V AC 10 hp at 460 V AC 10 hp at 575 V AC
System Voltage	600 V AC 230 V DC
Number of Poles	3P
Control Unit Type	Toggle
Phase	3 phases
Pilot Light	Red indicator 440...600 V
Starter Type	Non reversing
Electrical Connection	Screw clamp terminals
Wire Gauge	AWG 14...AWG 10 (copper)
Height	4.25 in
Width	2.44 in
Depth	2.75 in

### Environment

Certifications	CE UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05
----------------	---


---

NEMA Enclosure Rating	NEMA 1 plastic standard size
-----------------------	------------------------------

---

**Offer Sustainability**

---

RoHS (date code: YYWW)	Compliant - since 1545 - Schneider Electric declaration of conformity  <a href="#">Schneider Electric declaration of conformity</a>
------------------------	---

---

**Contractual warranty**

---

Warranty period	18 months
-----------------	-----------

---