

Product data sheet

Characteristics

2510MBW1

Manual Starter - NEMA 4 Polyester - 2P - Size M0
- No Indicator - 600VAC



Main

| | |
|-----------|----------------|
| Product | Manual Starter |
| Type | M |
| NEMA Size | M-0 |

Complementary

| | |
|----------------------------------|--|
| Control Unit | Push-button |
| Pilot Light | No indicator |
| Horsepower Rating | 2 hp at 230 V AC 1 phase 1 hp at 115 V AC 1 phase |
| System Voltage | 600 V AC |
| Number of Poles | 2P |
| Starter Type | Non reversing |
| Electrical Connection | Pressure wire clamp |
| Overload Relay Type | Melting alloy |
| Number of Thermal Units Required | 1 |
| Wire Gauge | AWG 14...AWG 8 (copper) |
| Auxiliary Contacts | Without |
| Height | 10.34 in |
| Width | 5.13 in |
| Depth | 5.78 in |

Environment

| | |
|-----------------------|---|
| Certifications | UL listed file E42243 CCN NLRV CSA LR60905 class 3211 05 |
| NEMA Enclosure Rating | NEMA 4/4X glass polyester |

Offer Sustainability

| | |
|------------------------|-----------------------|
| RoHS (date code: YYWW) | Will not be compliant |
| | Will not be compliant |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
