Product data sheet Characteristics

8501NR61

Relay socket - 11 pin - single tier - tubular - for 8510K relays







Main

Product range	8501N	
Product type	Relay Socket	
Pin shape	Tubular	
Number of pins	11	
[In] rated current	15 A at 300 V AC 5 A at 600 V AC	

Complementary

Electrical connection	Single tiered screw clamp terminals
Mounting type	DIN rail Panel
Package quantity	1

Environment

LIMIOIIIIEIIL		5
Certifications	CE CSA RoHS UL recognized	en Proposition of the proposition of the propositio
Height	54.8 mm	A. A
Width	2.32 in (59 mm)	
Depth	24.6 mm	

Offer Sustainability

		<u> </u>
		ätior
		ojla a
		Series
		ာ ပ
Main		Spec
Product range	8501N	s for
Product type	Relay Socket	Time to the second seco
Pin shape	Tubular	99
Number of pins	11	
[In] rated current	15 A at 300 V AC 5 A at 600 V AC	Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications
Complementary		de Jiji
Electrical connection	Single tiered screw clamp terminals	
Mounting type	DIN rail	
wounting type	Panel	etem
Package quantity	1	
English and a set		o b b
Environment	05	
Certifications	CE CSA	<u>8</u> .
	RoHS	or or
	UL recognized	tit Tute
Height	54.8 mm	Subst
Width	2.32 in (59 mm)	an an
Depth	24.6 mm	99
		tinte
Offer Sustainability		<u>8</u> .
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity	
- (Schneider Electric declaration of conformity	op «
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	a:
0 Mar 2010		

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
Contractual warranty	

Contractual warranty

Warranty period	18 months	