

Main

Ampere Rating	10A
Application	Heavy-duty design with modular construction
Approvals	UL Listed File: E78403 CCN NKCR - CSA Certified File: LR60905 Class 321103 - CE Marked
Coil Voltage	208VAC@60Hz
Contact Configuration	4 N.O.
Contact Rating	A600
Depth	3.95 Inches
Features	Straight-through wiring; Plug-in contact cartridges; Self-lifting pressure wire connectors; Replaceable coil
Height	3.50 Inches
Maximum Voltage Rating	600VAC
Mounting Type	Panel
Number of Poles	4-Pole
Operating Times	Pick-Up: 15ms - Drop-Out: 16ms
Phase	1-Phase
Relay Type	Control
Terminal Type	Screw Clamp
Type	X
Weight	2.0 Pounds
Width	2.23 Inches

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.