



Main

Range of product	Harmony 9001K
Product or component type	2 mechanically interlocked push-buttons
Device short name	9001K
Bezel material	Chromium plated metal

Complementary

Mounting diameter	30 mm
Shape of signaling unit head	Octagonal
Type of operator	1 latching, 1 spring return
Operator profile	Flush, cap/operator or lens colour:7 colours choice (unmarked marking)
Electrical shock protection class	Class II conforming to IEC 61140
Mechanical durability	5000000 cycles
Operating position	Any position
Product weight	0.54 kg

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14
Product certifications	NEMA UL 508
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Vibration resistance	7 gn (f= 2...500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn conforming to IEC 60068-2-27
IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13

NEMA 2
NEMA 3
NEMA 3R
NEMA 4
NEMA 6
