Product data sheet Characteristics

9001KR1BH6 PUSH BUTTON 600VAC 10A 30MM T-K



ľ	V	1	а	1	I	٢
•	٠	٠	_	٠.	۰	

		<u>.</u>
Range of product	Harmony 9001K	
Product or component type	Push-button	-
Device short name	К	<u> </u>
Type of operator	Spring return	
Operator profile	Black flush	
Operator additional information	Full guard in plastic	in the state of th

Complementary

Complementary	
Bezel material	Chromium plated metal
Mounting diameter	30 mm
Light source	Without
Light source	Without
Light block supply	Without supply
Contacts type and composition	1 NC
Connections - terminals	Screw clamp terminals
Operating position	Any position
[le] rated operational current	10 A (AC-15) 10 A (DC-13)
Contact operation	Standard
Device presentation	Complete product

Environment

Product certifications	CE	, , , , , , , , , , , , , , , , , , ,
	NEMA	
	UL listed file E42259 CCN NKCR	d d
	CSA LR 25490 class 3211 03	i.
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13	

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity	—————————————————————————————————————
	Schneider Electric declaration of conformity	 m
REACh	Reference not containing SVHC above the threshold	sclai

9001KR1BH6 may be replaced by any of the following products:



Complete control buttons 9001KR1U 30MM PUSH BUTTON FULL GUARD

Qty 1

Reason for Substitution: End of Life | Substitution date: 02 January 2013



Electrical functions 9001KA3 30MM CONTACT BLOCK 1NC

Qty 1

Reason for Substitution: End of Life | Substitution date: 02 January 2013