



### Main

|                                 |                         |
|---------------------------------|-------------------------|
| Range of product                | Harmony 9001K           |
| Product or component type       | Push-button             |
| Device short name               | K                       |
| Type of operator                | Spring return           |
| Operator profile                | Red recessed            |
| Operator additional information | Extended metallic guard |

### Complementary

|                                |                              |
|--------------------------------|------------------------------|
| Bezel material                 | Chromium plated metal        |
| Mounting diameter              | 30 mm                        |
| Light source                   | Without                      |
| Light source                   | Without                      |
| Light block supply             | Without supply               |
| Contacts type and composition  | 1 NO                         |
| Connections - terminals        | Screw clamp terminals        |
| Operating position             | Any position                 |
| [Ie] rated operational current | 10 A (AC-15)<br>10 A (DC-13) |
| Contact operation              | Standard                     |
| Device presentation            | Complete product             |

### Environment

|                           |  |
|---------------------------|--|
| Product certifications    | CE<br>NEMA<br>UL listed file E42259 CCN NKCR<br>CSA LR 25490 class 3211 03 |
| NEMA degree of protection | NEMA 1/2/3/3R/4/6/12/13  |

### Offer Sustainability

|                        |   |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 0921 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                  | Reference not containing SVHC above the threshold   |

