## Product data sheet Characteristics

## 9001SKR5G PUSHBUTTON OPERATOR 30MM SK +OPTIONS



Harmony 9001SK
Non-illuminated mushroom head push-button
9001SK
Plastic

## Complementary

Complementary		
Mounting diameter	30 mm	
CAD overall width	46 mm	;
CAD overall height	45 mm	
CAD overall depth	69 mm	<u> </u>
Product weight	0.095 kg	
Operating position	Any position	:
Shape of signaling unit head	Round	
Type of operator	Spring return	
Operator profile	Mushroom Ø 57 mm, cap/operator or lens colour:green (unmarked marking)	
Mechanical durability	5000000 cycles	
Operator additional information	Snap-in mushroom	

## Environment

Protective treatment	TC	<u></u>
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-2570 °C	v a
Electrical shock protection class	Class II conforming to IEC 61140	<u> </u>
IP degree of protection	IP66 conforming to IEC 60529	
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 4	er This documentation is not i
Standards	CSA C22.2 No 14	

	RoHS compliant EN/IEC 60947-5-1 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508
Product certifications	NEMA UL 508 CSA LR25490 class 3211 03 UL listed file E78403 CCN NKCR
Vibration resistance	7 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn conforming to IEC 60068-2-27