Product data sheet Characteristics

XVBC21 INDICATING BANK ACCESSORIES 70MM +OPTIONS





| Range of product | Harmony XVB Universal | | |
|--|-----------------------|--|--|
| Product or component type | Base unit with cover | | |
| Component name | XVBC | | |
| Material Glass reinforced polyamide base unit Polycarbonate cover unit | | | |

Complementary

| Fixing mode | Direct or tube fixing | |
|-------------------------------|--|--|
| Mounting diameter | 70 mm | |
| Product destination | Banks without flash discharge tube unit | |
| Electrical connection | 1 connector for standard input | |
| Cable entry | Bottom or side entry | |
| Assembly style | Customer assembly, up to 5 units | |
| Terminals description ISO n°1 | (COM-4)PW (COM-2)PW (GND)GROUND (COM-3)PW (COM-1)PW (COM-5)PW | |
| Product weight | 0.19 kg | |

Environment

| LIMIOIIIIEIIL | | Ť. |
|-------------------------------------|--|-------------------|
| Product certifications | GOST CSA C22-2 No 14 CCC UL 508 | ided as a substit |
| Standards | EN/IEC 60947-5-1 | |
| Protective treatment | TC | is not |
| Ambient air temperature for storage | -4070 °C | |
| NEMA degree of protection | NEMA 4X indoor UL 508 | me mentk |

Contractual warranty

| | • | | | |
|-----------------|---|-----------|--|--|
| Warranty period | | 18 months | | |