

# 9070TF300D1

## TRANSFORMER CONTROL 300VA

### 240/480V-120V

Product availability : Stock - Normally stocked in distribution facility



Price\*\* : 312.00 USD



### Main

Product or component type	Industrial Control Transformer
Power Rating	300 VA
Primary Voltage	240 x 480 V 220 x 440 V 230 x 460 V
Secondary Voltage	110 V 120 V 115 V
Type	TF

### Complementary

Number of Phases	1 phase
Power Rating	300 VA UL 300 VA CSA 300 VA NOM 200 VA CE
Primary to Secondary Voltage	220 x 440 V 110 V 230 x 460 V 115 V 240 x 480 V 120 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	80 °C
Electrical connection	Screw clamp terminals
Height	130.30 mm (5.13 in)
Width	114.30 mm (4.5 in)
Depth	120.40 mm (4.74 in)
Material	Copper winding
Fingersafe Cover Compatibility	FSC2

## Environment

Product certifications	CSA file LR37055 guide 184-N-90 CE UL listed file E61239
Enclosure Type	Not rated (open device)
Insulation temperature	266 °F (130 °C)

## Ordering and shipping details

Category	16203 - 9070 TF (NOT T) 250-1000VA
Discount Schedule	CP8
GTIN	00785901904878
Package weight(Lbs)	4.39 kg (9.68 lb(US))
Returnability	Yes
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------