



### Main

Range of product	Type S
Product or component type	Selector switch
Product destination	Contactors Starter

### Complementary

NEMA size	0 1 2 3 00
Marking	ON-OFF
Mounting mode	Panel-mounted
Rated breaking capacity	3 A at 120 V AC for inductive control circuit per UL 508 1.5 A at 240 V AC for inductive control circuit per UL 508 0.6 A at 600 V AC for inductive control circuit per UL 508 5 A at 600 V AC for resistive control circuit per UL 508

### Environment

NEMA degree of protection	NEMA 1
product certifications	CSA UL listed UL recognized

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1545 - Schneider Electric declaration of conformity	Compliant - since 1545 - Schneider Electric declaration of conformity

### Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.