

# Product data sheet

## Characteristics

# HOM2040L125PRB

## HOM OUTD 125A MLO 20/40CIR

Product availability : Stock - Normally stocked in distribution facility



Price\* : 383.00 USD



### Main

Product or component type	Load Center
Range of product	Homeline
Load center type	Main lugs
Line Rated Current	125 A
Number of spaces	20
Number of circuits	40
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Electrical connection	Lugs

### Complementary

Short-circuit current	10 kA
Number of tandem circuit breakers	20
Phase	1 phase
System Voltage	120/240 V AC
AWG gauge	AWG 6...AWG 2/0 [Space(aluminium) AWG 6...AWG 1/0 [Space(copper)
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Material	Tin plated aluminium busbar
Enclosure material	Welded galvanized steel
Surface finish	Baked enamel grey
Box number	4R

### Environment

Product certifications	UL E-6294
------------------------	-----------

## Ordering and shipping details

Category	00145 - HOM LC&CVR,12-42CKT NEMA3R
Discount Schedule	DE3C
GTIN	00785901847557
Nbr. of units in pkg.	1
Package weight(Lbs)	23.800000000000001
Returnability	Y
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations