Product data sheet Characteristics

HOM2040M100PCVP HOM VALPK INDR 100A MB 20/40CIR

Product availability: Stock - Normally stocked in distribution facility



Price*: 528.00 USD



Main

Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	100 A	
Number of spaces	20	
Number of circuits	40	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Provided equipment	Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC	

Complementary

Main		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	100 A	
Number of spaces	20	
Number of circuits	40	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
* * * * * * * * * * * * * * * * * * * *	Combination flush/surface cover Lugs	
Cover type Electrical connection Provided equipment		
Electrical connection Provided equipment Complementary	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled	
Electrical connection Provided equipment Complementary Short-circuit current	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC	
Electrical connection Provided equipment Complementary Short-circuit current Number of tandem circuit breakers	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC 22 kA	
Electrical connection	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC 22 kA 20	
Electrical connection Provided equipment Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC 22 kA 20 1 phase	
Electrical connection Provided equipment Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 6AWG 1 [Space(aluminium)	
Electrical connection Provided equipment Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 6AWG 1 [Space(aluminium) AWG 6AWG 3 [Space(copper)	
Electrical connection Provided equipment Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Cover finish	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 6AWG 1 [Space(aluminium) AWG 6AWG 3 [Space(copper) 3-wire	
Electrical connection Provided equipment Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Cover finish Material	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 6AWG 1 [Space(aluminium) AWG 6AWG 3 [Space(copper) 3-wire Gray baked enamel	
Electrical connection Provided equipment Complementary Short-circuit current Number of tandem circuit breakers Phase	Lugs Circuit breaker [Space(2) 1P 20 A 120/240 V AC Circuit breaker [Space(1) 2P 100 A 120/240 V AC main supply ready assembled Circuit breaker [Space(1) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 6AWG 1 [Space(aluminium) AWG 6AWG 3 [Space(copper) 3-wire Gray baked enamel Tin plated aluminium busbar	

Environment

|--|

Ordering and shipping details

Category	00185 - MISC. HOM LOAD CENTERS
Discount Schedule	DE3C
GTIN	00785901977339
Nbr. of units in pkg.	1
Package weight(Lbs)	22.4000000000002
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	