# Product data sheet Characteristics

# QO130L200PG

QO LoadCenter, Main Lugs, 200A, 1PH-3W, 30SP, NEMA 1, Incl. Gnd.Bar, PON

Product availability: Stock - Normally stocked in distribution facility



Price\*\*: 597.00 USD



#### Main

Wall		
Product	Load Center	7
Marketing Trade Name	QO	
Cover type	Order separately	***************************************

### Complementary

Load Center Type	Main lugs
Line Rated Current	200 A
Number of spaces	30
Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	40
Maximum Number of Tandem Breakers	10
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 6250 kcmil aluminium/copper Lugs
Electrical Connection	Lugs
Grounding Bar	Grounding bar included (not installed)
Electrical connection	Lugs
Wiring configuration	3-wire
Busbar Material	Tin plated copper busbar
Enclosure Material	Welded sheet steel
Cover Finish	Baked enamel grey
Box number	9
Height	29.84 in (758 mm)
Width	14.25 in (362 mm)

Tightening torque	28.25 N.m (250 lbf.in) AWG 4250 kcmil) 28.25 N.m (250 lbf.in) AWG 4300 kcmil)
F. C. C. C.	
Environment	
Enclosure Rating	NEMA 1 indoor
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL listed
Ordering and shipping details	
Category	10003 - QO PON 1PH LC,12-60 CKT, ML N1
Discount Schedule	DE3A
GTIN	00785901219248
Returnability	Yes
Country of origin	US
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

## Contractual warranty

Circularity Profile

Warranty	18 months	S	

No need of specific recycling operations