


Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

XX9V3A1D2M12



Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Sensing Window:
 Far Limit:
 Sensing Range: 102.0 mm to 1.0 mm (4.0 in to 39.0 in)
 Circuit Type:
 Output Mode: Direct 4-20 mA
 Volts Type: DC
 Voltage Range: 15-24 VDC
 Max Load: 100 mA
 Current Consumption:
 Sonic Frequency: 180 Hz
 Temp Range: - 40° to 80° C (-40° to 176°F)
 NEMA Type: NEMA 4X (indoor use only)
 IP Rating: IP67
 Standards: UL, CE, CSA, Rohs

Specification:

Sensor Type: Analog
 Description: Ultrasonic Sensor, Analog, Barrel, 15-24 VDC
 Body Style: Barrel
 Diameter: 30 mm
 Housing Material: Valox PBT Plastic
 Face Material: Glass Epoxy
 Field Configurable:
 Functionality: 350 ohms
 Cable Size:
 Connector Type: M12
 Special Features: Tamper Proof with PB100 Pushbutton Accessory