

STANLEY® LEVERLOCK® TAPE RULES

- Push-release self-locking mechanism controls blade retraction.
- Polymer-coated blade withstands abrasion.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.
- High-impact, yellow ABS case is over molded with soft-grip rubber for maximum comfort, slip-resistant grip, and durability.



Product #	Blade Length	Blade Width	Stud Marking	Stud Marking
30-810	12 ft (3 m)	1/2 in (13 mm)	16 in	19.2 in
	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.			
30-812	16 ft (5 m)	3/4 in (19 mm)	16 in	19.2 in
	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.			
30-825	25 ft (7.6 m)	1 in (25 mm)	16 in	19.2 in
	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.			
30-824L	8 m/26 ft cm graduation	1 in (25 mm)	16 in	19.2 in
	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.			
30-830W	30 ft (9.1 m)	1 in (25 mm)	16 in	19.2 in
	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.			

STANLEY® LEVERLOCK® FRACTIONAL TAPE RULES WITH MAGNETIC TIP

- Push-release self-locking mechanism controls blade retraction.
- Polymer-coated blade withstands abrasion.
- Magnetic end hook holds securely to metal surfaces.
- High-impact ABS case with durable rubber holds up to heavy use.
- 16" and 19.2" stud center markings simplify framing jobs.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.
- Fractional read blade graphics for quick and easy measurements.
- Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch.
- Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.



Product #	Blade Length	Blade Width	Stud Marking	Stud Marking	Color	End Hook
33-270	25 ft (7.6 m)	1 in (25 mm)	16 in	19.2 in	Orange	Magnetic
33-281	25 ft (7.6 m)	1 in (25 mm)	16 in	19.2 in	Yellow	Magnetic

