

STANLEY® TAPE RULES

- Polymer-coated blade withstands abrasion.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.
- Fractional read blade graphics for quick and easy measurements (only on 30-454).
- Versatile 1/2", 3/4", and 1" wide blades and 7' standout (1" wide blades only).
- Ergonomically designed high-impact, yellow ABS case.



Product #	Blade Length	Blade Width	Stud Marking	Stud Marking
30-506	6 ft (1.8 m)	1/2 in (13 mm)	16 in	19.2 in
Top edge: Major scale numbered in consecutive feet; minor scale numbered in consecutive inches after each foot; graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches; first twelve inches graduated in 32nds of an inch; remainder in 16ths of an inch.				
30-485	12 ft (3 m)	1/2 in (13 mm)	16 in	19.2 in
Top edge: Major scale numbered in consecutive feet; minor scale numbered in consecutive inches after each foot; graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches; first twelve inches graduated in 32nds of an inch; remainder in 16ths of an inch.				
30-495	16 ft (5 m)	3/4 in (19 mm)	16 in	19.2 in
Top edge: Major scale numbered in consecutive feet; minor scale numbered in consecutive inches after each foot. First twelve inches graduated in 32nds of an inch; remainder in 16ths of an inch. Bottom edge: Numbered in consecutive inches; first twelve inches graduated in 32nds of an inch; remainder in 16ths of an inch.				
30-496	5 m/16 ft cm graduation	3/4 in (19 mm)	16 in	19.2 in
Top edge: Numbered in consecutive inches; first twelve inches graduated in 32nds of an inch, remainder graduated in 16ths of an inch; marked every 12 inches. Bottom edge: Numbered in consecutive cm; graduated in ; marked every 10 cm.				
30-456	8 m/26 ft cm graduation	1 in (25 mm)	16 in	19.2 in
Top edge: Numbered in consecutive inches; first twelve inches graduated in 32nds of an inch; remainder graduated in 16ths of an inch; marked every 12 inches. Bottom edge: Numbered in consecutive cm; graduated in ; marked every 10 cm.				
30-454	25 ft (7.6 m) cm graduation	1 in (25 mm)	16 in	19.2 in
Major scale numbered in consecutive feet; minor scale numbered in consecutive inches; graduated in 16ths of an inch. Numerical readouts every 8th of an inch.				
30-455	25 ft (7.6 m)	1 in (25 mm)	16 in	19.2 in
Top edge: Major scale numbered in consecutive feet; minor scale numbered in consecutive inches after each foot; graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches; graduated in 16ths of an inch.				
30-464	30 ft (9.1 m)	1 in (25 mm)	16 in	19.2 in
Top edge: Major scale numbered in consecutive feet; minor scale numbered in consecutive inches after each foot; graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches; graduated in 16ths of an inch.				

STANLEY® HIGH-VISIBILITY TAPE RULE

- 7' blade standout.
- Polymer-coated blade withstands abrasion.
- High-impact, high-visibility green ABS case is over molded with soft-grip rubber.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Product #	Blade Length	Blade Width	Stud Marking	Stud Marking
30-305	25 ft (7.6 m)	1 in (25 mm)	16 in	19.2 in
Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.				

