

STANLEY® FATMAX® CLOSED CASE LONG TAPE



- 3-to-1 Gear drive for fast rewinds.
- Polymer-coated blade withstands abrasion.
- Steel roller cage protects case from being cut by blade during rewind.
- High-impact, yellow ABS case is over molded with soft-grip rubber for maximum comfort, slip-resistant grip, and durability.
- Corrosion-resistant Tru-Zero™ folding end hook for accurate measurements.
- Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch.



Product #	Blade Length	Blade Width	Stud Marking
34-130	100 ft (30 m)	3/8 in (9.5 mm)	16 in

STANLEY® CLOSED CASE LONG TAPES

- High impact, high visibility yellow ABS case.
- Polymer-coated blade withstands abrasion for a long life.
- Easy wind drum for easy retraction.
- Easy to read markings.
- Lock ring recoils neatly into contoured case.
- Belt clip for hands-free use and convenient transportation.
- Corrosion-resistant Tru-Zero™ folding end hook for accurate measurements.



Product #	Blade Length	Blade Width	Stud Marking
34-103	50 ft (15 m)	3/8 in (9.5 mm)	16 in
	Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch.		
34-106	100 ft (30 m)	3/8 in (9.5 mm)	16 in
	Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch.		

STANLEY® FATMAX® OPEN REEL LONG TAPE



- Rewinds 3X faster* with 3:1 gear drive.
- 64 fiberglass strands provide 2X blade strength*.
- Extra width 3/4", 2-color blade for easy readability in most lighting conditions.
- 2-sided blade graphics with fractional inch/decimal foot scales for versatility.
- Reinforced blade end for long life.
- End loop for easy pulling and anchoring.
- High-impact ABS case with durable rubber grip holds up to heavy use.
- Corrosion-resistant Tru-Zero™ folding end hook for accurate measurements.

* Than base Stanley® model



Product #	Blade Length	Blade Width
34-812	100 ft (30 m)	3/4 in (19 mm)

