

STANLEY® COMPO-CAST® SLIMLINE SOFT-FACE HAMMERS

- Slimline model offers unique profile for assembly and repair applications in confined areas.
- Uni-Cast™ construction of non-ferrous materials eliminates sparking and won't absorb liquids.
- No exposed metal on face, head or shaft.
- Dead blow function eliminates bounceback when striking hardened surfaces.
- Soft face helps prevent marring.
- Steel reinforced handle provides strength and resists breaking on overstrike.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
57-540	5 oz (142 g)	2-15/16 in (74 mm)	29/32 in (23 mm)	9-1/2 in (241 mm)
57-541	14 oz (397 g)	4-3/16 in (106 mm)	1-19/64 in (33 mm)	10-1/2 in (267 mm)
57-542	18 oz (510 g)	4-1/4 in (108 mm)	1-33/64 in (38 mm)	12-1/8 in (308 mm)
57-543	21 oz (595 g)	5-1/4 in (133 mm)	1-17/32 in (39 mm)	12-7/8 in (327 mm)

STANLEY® COMPO-CAST® SOFT-FACE SLEDGE HAMMERS

- Non-sparking, soft-face sledgehammers.
- Uni-Cast™ construction of non-ferrous materials eliminates sparking and won't absorb liquids.
- No exposed metal on face, head or shaft.
- Dead blow function eliminates bounceback when striking hardened surfaces.
- Soft face helps prevent marring.
- Steel reinforced handle provides strength and resists breaking on overstrike.
- Urethane covering helps reduce noise.
- Flat area on head allows upright storage.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
57-550	5 lbs (2.26 kg)	7 in (178 mm)	2-55/64 in (73 mm)	19-5/8 in (498 mm)
57-551	8 lbs (3.62 kg)	7-1/8 in (181 mm)	2-61/64 in (75 mm)	29-7/8 in (759 mm)
57-552	10.5 lbs (4.76 kg)	8-1/8 in (206 mm)	3-25/64 in (86 mm)	29-7/8 in (759 mm)
57-554	11.5 lbs (5.21 kg)	8-1/8 in (206 mm)	3-25/64 in (86 mm)	36-18 in (918 mm)

STANLEY® HICKORY HANDLE SLEDGE HAMMERS

- Forged head is heat-treated and tempered for increased durability.
- Traditional, high quality hickory handle.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
56-808	8 lbs (3.62 kg)	6-7/16 in (164 mm)	2-5/16 in (59 mm)	34-1/4 in (870 mm)
56-810	10 lbs (4.53 kg)	7-1/8 in (181 mm)	2-3/8 in (60 mm)	35 in (889 mm)
56-812	12 lbs (5.44 kg)	7-1/2 in (191 mm)	2-5/8 in (67 mm)	35 in (889 mm)
56-816	16 lbs (7.25 kg)	8-3/8 in (213 mm)	2-13/16 in (71 mm)	35 in (889 mm)

