

## LONG HANDLE PREMIUM PEAR HEAD RATCHETS

Small pear head design for access in tight, hard to reach work areas.



- Sealed design helps prevent debris from entering the ratchet mechanism reducing wear. Also, helps to keep lubrication contained within the components. Patent pending design.
- Low profile reversing lever design for quick, one-hand operation.
- Contoured, ergonomically-designed handle for comfort. Knurled bands allow for increased grip and slip resistance.
- Double nickel chrome plated for enhanced corrosion protection or black oxide finish.
- Field repairable.



## **REROSPACE PREMIUM PEAR HEAD RATCHETS**

- Vertical hole drilled in drive plug, designed for installation of frangible collars on threaded pins.
- Unique 45-tooth gear pawl design provides 8° ratcheting angle while maximizing ultimate torque.
- Thin head design for access into tight work areas.
- Reversing lever designed for quick, one-hand operation.
- Full polish nickel chrome plated.

Product #	Drive Size (in)	Finish	Overall Length (in)	Weight (lbs)	Repair Kit
J4749XLHS	1/4	Full Polish	5-45/64	0.25	J4749XLHSRK
J5249XLHS	3/8	Full Polish	8-1/2	0.86	J5249XLHSRK
					ASME B107.500

## *REROSPACE CLASSIC PEAR HEAD RATCHETS*

- Vertical hole drilled in drive plug, designed for installation of frangible collars on threaded pins.
- Metal spring clip on drive plug for positive socket retention.
- 24-tooth gear provides 15° articulation angle.
- Thin head design for access into tight work areas.
- > Reversing lever designed for quick, one-hand operation.
- Full polish double nickel chrome plated

Product #	Drive Size (in)	Finish	Overall Length (in)	Weight (lbs)	Repair Kit
J4749HS	1/4	Full Polish	5	0.25	J4749RK
J5249HS	3/8	Full Polish	7	0.62	J5249HSRK
				<u></u>	■ ASME B107.500

## STUBBY CLASSIC PEAR HEAD RATCHETS

- Robust 24-tooth design with 15° arc swing.
- Alloy steel drive gear for strength and durability.
- Low profile head for access in constricted areas.
- Reversing lever design for guick, one-hand operation.
- > Knurled slip-resistant grip.

Product #	Drive Size (in)	Finish	Overall Length (in)	Weight (lbs)	Repair Kit
J5248S	3/8	Full Polish	5	0.28	J5249RK
				<b>=</b>	ASME B107.500









ASME B107.500

PREMIUM

