

**3/8" DRIVE UNIVERSAL SPARK PLUG SOCKETS - 6 POINT**

- ▶ With rubber insert.



Product #	Size (in) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Overall Length (in) (L)	Weight (lbs)
<b>J5020-70A</b>	5/8	27/32	23/32	5/16	3-19/64	0.26
<b>J5026-50A</b>	13/16	1-1/16	23/32	5/16	3-3/8	0.34

**3/8" DRIVE DRAG LINK SOCKET**

Product #	Size (in)	Tip Width (in)	Overall Length (in)	Weight (lbs)
<b>J5244</b>	11/16	1/8	1-1/8	0.06



**3/8" DRIVE SLOTTED SCREWDRIVER BIT SOCKETS**

Product #	Tip Size	Tip Width (in)	Overall Length (in)	Weight (lbs)
<b>J5246</b>	1/4	1/32	1-13/16	0.01
<b>J5240A</b>	5/16	3/64	3	0.13



**3/8" DRIVE PHILLIPS® SCREWDRIVER BIT SOCKETS**

- ▶ Two piece design allows replacement of worn bits.
- ▶ Bit holders have a hex opening to hold the bit allowing the bit holder to take the full load of torque.

Product #	Tip Size	Overall Length (in)	Weight (lbs)
<b>J5241</b>	#2	1-31/32	0.11
<b>J5242</b>	#3	1-31/32	0.12
<b>J5243</b>	#4	1-31/32	0.12



**3/8" DRIVE TORX® SCREWDRIVER BIT SOCKETS**

Product #	Torx® Size	Bit Length (in)	Overall Length (in)	Weight (lbs)
<b>J5239-10W</b>	T10	5/8	1-23/32	0.10
<b>J5239-15W</b>	T15	5/8	1-23/32	0.10
<b>J5239-20W</b>	T20	5/8	1-23/32	0.10
<b>J5239-25W</b>	T25	5/8	1-23/32	0.10
<b>J5239-27W</b>	T27	5/8	1-23/32	0.10
<b>J5239-30W</b>	T30	7/8	1-23/32	0.12
<b>J5239-40W</b>	T40	7/8	1-23/32	0.11
<b>J5239-45W</b>	T45	7/8	1-23/32	0.12
<b>J5239-50W</b>	T50	7/8	1-23/32	0.12
<b>J5239-55W</b>	T55	7/8	1-23/32	0.13

