



1/2" DRIVE SOCKETS - 12 POINT

- › Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- › TorquePlus™ features apply.



Product #	Size (in) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J5408T	1/4	1/4	23/32	23/64	23/32	1-34/64	0.11
J5410	5/16	17/32	55/64	23/64	23/32	1-34/64	0.11
J5412	3/8	9/16	55/64	23/64	7/8	1-31/64	0.11
J5414	7/16	43/64	55/64	23/64	7/8	1-31/64	0.11
J5416	1/2	47/64	55/64	23/64	7/8	1-31/64	0.11
J5417	17/32	7/8	55/64	23/64	23/32	1-31/64	0.12
J5418	9/16	13/16	55/64	23/64	51/64	1-1/2	0.13
J5419	19/32	7/8	55/64	9/16	21/32	1-1/2	0.13
J5420	5/8	7/8	7/8	9/16	21/32	1-1/2	0.14
J5421	21/32"	61/64	61/64	9/16	21/32	1-1/2	0.15
J5422	11/16	61/64	61/64	9/16	21/32	1-1/2	0.15
J5424	3/4	1-1/32	1-1/64	11/16	21/32	1-1/2	0.15
J5425	25/32	1-1/16	1-5/64	11/16	21/32	1-1/2	0.20
J5426	13/16	1-3/32	1-5/64	11/16	21/32	1-1/2	0.23
J5428	7/8	1-11/64	1-3/16	11/16	45/64	1-9/16	0.26
J5429	29/32	1-3/16	1-3/16	13/16	45/64	1-9/16	0.30
J5430	15/16	1-1/4	1-1/4	13/16	45/64	1-9/16	0.33
J5431	31/32	1-9/32	1-9/32	13/16	45/64	1-9/16	0.35
J5432	1	1-21/64	1-5/16	27/32	45/64	1-9/16	0.38
J5434	1-1/16	1-13/32	1-25/64	13/16	25/32	1-5/8	0.42
J5436	1-1/8	1-31/64	1-31/64	15/16	29/32	1-3/4	0.47
J5438	1-3/16	1-9/16	1-17/32	59/64	29/32	1-3/4	0.59
J5440	1-1/4	1-39/64	1-37/64	1	7/8	1-3/4	0.66
J5442	1-5/16	1-21/32	1-41/64	27/32	1-19/64	1-55/64	0.69
J5444	1-3/8	1-25/32	1-5/8	25/32	1-19/64	2	0.79
J5446	1-7/16	1-59/64	1-5/8	27/32	1-19/64	2-1/8	0.98
J5448	1-1/2	1-63/64	1-5/8	27/32	1-19/64	2-1/4	1.12



AS954E S3.8.1

ASME B107.1

