

1/2" DRIVE BLACK OXIDE SOCKETS - 12 POINT

- Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- TorquePlus™ features apply.



Product #	Size (in) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J5412B	3/8	9/16	55/64	23/64	7/8	1-1/2	0.10
J5414B	7/16	43/64	55/64	23/64	7/8	1-1/2	0.12
J5416B	1/2	47/64	55/64	23/64	7/8	1-1/2	0.12
J5418B	9/16	13/16	55/64	23/64	51/64	1-1/2	0.12
J5420B	5/8	7/8	7/8	9/16	21/37	1-1/2	0.12
J5422B	11/16	61/64	61/64	9/16	21/32	1-1/2	0.15
J5424B	3/4	1-1/32	1-1/32	11/16	21/32	1-1/2	0.17
J5426B	13/16	1-3/32	1-3/32	11/16	21/32	1-1/2	0.20
J5428B	7/8	1-11/64	1-11/64	11/16	45/64	1-9/16	0.25
J5430B	15/16	1-1/4	1-1/4	13/16	45/64	1-9/16	0.27
J5432B	1	1-5/16	1-3/16	27/32	45/64	1-9/16	0.31
J5434B	1-1/16	1-25/64	1-25/64	13/16	25/32	1-5/8	0.37
J5436B	1-1/8	1-31/64	1-31/64	15/16	29/32	1-3/4	0.44
J5438B	1-3/16	1-17/32	1-17/32	59/64	29/32	1-3/4	0.45
J5440B	1-1/4	1-37/64	1-37/64	1	7/8	1-21/32	0.43
J5442B	1-5/16	1-41/64	1-41/64	1-27/32	1-19/64	1-3/4	0.52
J5444B	1-3/8	1-51/64	1-5/8	1-31/32	1-19/64	2	0.67
J5446B	1-7/16	1-59/64	1-5/8	1-27/32	1-19/64	2-1/8	0.80
J5448B	1-1/2	1-63/64	1-5/8	1-27/32	1-19/64	2-1/4	0.85

AS954E S3.8.1

ASME B107.1

1/2" DRIVE DEEP SOCKETS - 12 POINT

- Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- TorquePlus™ features apply.



Product #	Size (in) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J5312	3/8	9/16	7/8	1/4	2-39/64	3-1/4	0.28
J5314	7/16	9/16	7/8	23/64	2-39/64	3-1/4	0.28
J5316	1/2	47/64	55/64	25/32	2-39/64	3-1/4	0.29
J5318	9/16	13/16	27/32	15/16	2-39/64	3-1/4	0.29
J5320	5/8	7/8	7/8	1-7/32	2-39/64	3-1/4	0.30
J5322	11/16	31/32	31/32	1-7/32	2-39/64	3-1/4	0.42
J5324	3/4	1-3/64	1-3/64	1-7/32	2-39/64	3-1/4	0.42
J5326	13/16	1-3/32	1-3/32	1-7/32	2-39/64	3-1/4	0.52
J5328	7/8	1-11/64	1-11/64	1-7/32	2-39/64	3-1/4	0.58
J5330	15/16	1-1/4	1-1/4	1-7/32	2-39/64	3-1/4	0.67
J5332	1	1-21/64	1-21/64	1-7/32	2-29/64	3-1/4	0.67
J5334	1-1/16	1-13/32	1-13/32	1-9/32	2-29/64	3-1/4	0.75
J5336	1-1/8	1-1/2	1-1/2	1-5/32	2-29/64	3-1/4	0.83
J5340	1-1/4	1-9/16	1-9/16	1-13/32	2-29/64	3-1/4	1.06
J5338	1-3/16	1-35/64	1-35/64	1-7/64	2-1/4	3-1/4	0.83
J5342	1-5/16	1-7/8	1-5/8	27/32	2-1/4	3-1/2	1.06
J5344	1-3/8	1-7/8	1-5/8	61/64	2-1/4	3-1/2	1.23
J5346	1-7/16	2-1/16	1-5/8	61/64	2-1/4	3-1/2	1.27
J5348	1-1/2	2-1/16	1-5/8	1	2-1/4	3-1/2	1.58

AS954E S3.8.1

ASME B107.1