

## 1/4" DRIVE METRIC UNIVERSAL IMPACT SOCKETS - 12 POINT

Product #	Size (mm)	Drive End		Overall	
		Outside Dia. (in) (C)	Length (in) (L)	Weight (lbs)	
J66506MP	6	5/8	1-9/32	0.27	
J66507MP	7	5/8	1-5/16	0.27	
J66508MP	8	5/8	1-11/32	0.28	
J66509MP	9	5/8	1-3/8	0.30	
J66510MP	10	5/8	1-7/16	0.31	
J66511MP	11	5/8	1-1/2	0.31	
J66512MP	12	5/8	1-17/32	0.32	
J66513MP	13	5/8	1-19/32	0.32	
J66555MP	5.5	5/8	1-1/4	0.27	



## 1/4" DRIVE IMPACT UNIVERSAL JOINT

- › Tight tolerances for snug fit on fastener.
- › Used wherever powered drive tools are used to install or remove fasteners.
- › Designed to withstand the high torque and force associated with impact tools in repetitive application.
- › Features two through holes and a groove to accept a Proto® Retaining Ring or pin and O-ring to help secure the socket to the drive tool anvil.
- › Position at appropriate angle to turn fasteners where obstructions prevent a straight application.
- › Ball and spring design which allows for a 30° working angle.
- › Smooth 360° rotation.

Product #	Drive End Outside Dia. (in) (C)	Overall Length (in) (L)	Weight (lbs)
J66170P	5/8	1-3/8	0.27



## 1/4" DRIVE TORX® IMPACT SOCKETS

- › Made of alloy steel.
- › Black oxide finish.
- › For use with Torx® style fasteners.



Product #	Torx® Size	Nut End Outside Dia. (B)	Drive End Outside Dia. (C)	Nut Depth (D)	Overall Length (in)	Weight (lbs)
J6904TX	E4	1/4	7/16	13/64	1	0.03
J6905TX	E5	1/4	7/16	7/32	1	0.04
J6906TX	E6	5/16	7/16	15/64	1	0.02
J6907TX	E7	21/64	1/2	9/32	1	0.03
J6908TX	E8	3/8	19/64	19/64	1	0.03
J6910TX	E10	1/2	1/2	11/32	1	0.05
J6912TX	E12	9/16	9/16	25/64	1	0.05

