



1/2" DRIVE IMPACT SOCKETS - 12 POINT

- › Proto® 12 Point Impact Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- › TorquePlus™ features apply.
- › Socket size stamped on tool for easy identification.
- › Side locking hole.



Product #	Size (in) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J7412	3/8	41/64	15/16	11/32	27/32	1-1/2	0.16
J7414	7/16	23/32	15/16	13/32	27/32	1-1/2	0.17
J7416	1/2	51/64	15/16	13/32	27/32	1-1/2	0.18
J7418	9/16	7/8	15/16	7/16	27/32	1-1/2	0.19
J7420	5/8	1	1	1/2	27/32	1-1/2	0.20
J7422	11/16	1-1/32	1-1/32	1/2	27/32	1-1/2	0.21
J7424	3/4	1-7/64	1-7/64	51/64	27/32	1-1/2	0.23
J7426	13/16	1-13/64	1-13/64	11/16	31/32	1-5/8	0.30
J7428	7/8	1-9/32	1-9/32	43/64	31/32	1-5/8	0.34
J7430	15/16	1-23/64	1-23/64	51/64	1-3/32	1-3/4	0.42
J7432	1	1-1/2	1-1/2	25/32	1-3/32	1-3/4	0.53
J7434	1-1/16	1-33/64	1-33/64	25/32	1-3/32	1-3/4	0.52
J7436	1-1/8	1-19/32	1-19/32	25/32	1-1/32	2	0.62
J7438	1-3/16	1-3/4	1-3/4	3/4	1-1/64	2	0.80
J7440	1-1/4	1-3/4	1-3/4	3/4	1	2	0.77
J7442	1-5/16	1-3/4	1-3/4	13/16	63/64	2	0.72
J7444	1-3/8	1-51/64	1-5/8	13/16	1-3/32	2-1/8	0.70
J7446	1-7/16	1-59/64	1-5/8	1	1-37/64	2-15/64	0.80
J7448	1-1/2	2	1-5/8	1	1-37/64	2-15/64	0.97



AS954E S3.8.1

ASME B107.2

1/2" DRIVE METRIC IMPACT SOCKETS - 12 POINT

- › Proto® 12 Point Impact Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- › TorquePlus™ features apply.
- › Socket size stamped on tool for easy identification.
- › Side locking hole.



METRIC

Product #	Size (mm) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J7410MT	10	39/64	57/64	1/4	21/32	1-1/2	0.16
J7411MT	11	21/32	15/16	9/32	21/32	1-1/2	0.16
J7412MT	12	11/16	15/16	5/16	21/32	1-1/2	0.18
J7413MT	13	47/64	15/16	11/32	21/32	1-1/2	0.15
J7414MT	14	51/64	15/16	3/8	21/32	1-1/2	0.15
J7415MT	15	27/32	15/16	7/16	21/32	1-1/2	0.16
J7416MT	16	7/8	15/16	7/16	21/32	1-1/2	0.15
J7417MT	17	15/16	15/16	7/16	21/32	1-1/2	0.15
J7418MT	18	1	1	7/16	21/32	1-1/2	0.18
J7419MT	19	1-1/32	1-1/32	27/32	21/32	1-1/2	0.17
J7420MT	20	1-1/8	1-1/16	27/32	21/32	1-1/2	0.18
J7421MT	21	1-3/16	1-1/8	27/32	21/32	1-1/2	0.43
J7422MT	22	1-1/4	1-3/16	27/32	21/32	1-1/2	0.25
J7423MT	23	1-5/16	1-1/4	27/32	21/32	1-1/2	0.30
J7424MT	24	1-13/32	1-5/16	27/32	21/32	1-1/2	0.32
J7430MT	30	1-11/16	1-5/8	1-1/32	1-11/32	2	0.58
J7432MT	32	1-25/32	1-5/8	1-1/32	1-11/32	2	0.64



AS954E S3.8.1

ASME B107.33M

