

Precision Torque



MICROMETER TORQUE WRENCH - RATCHETING HEAD

- Ft / Lbs.
- Calibrated to +/- 3% clockwise direction and +/- 6% counter clockwise at 20% to 100% of full scale.
- Calibration is accomplished by manual loading the torque wrenches.
- Manufactured to meet standard industrial torque applications, general industry, heavy equipment, and maintenance.



Product ID No.	Drive Size	Torque Range			Head Length	Head Width	Head Depth	Weight lbs.	Storage Case	Ratchet Repair Kit	ASME Spec.
		Min.	Max.	Increments							
J6006C	3/8 Inch	16 ft. lbs.	80 ft. lbs.	0.5 ft. lbs.	15-1/2"	1-7/16"	1-1/64"	3 lbs.	J6006PBF	J6006RK	B107.14M
J6012C	3/8 Inch	20 ft. lbs.	100 ft. lbs.	0.5 ft. lbs.	17"	1-7/16"	1-1/64"	3.3 lbs.	J6006PBF	J6006RK	B107.14M
J6008C	1/2 Inch	16 ft. lbs.	80 ft. lbs.	0.5 ft. lbs.	15-1/2"	1-7/16"	1-7/32"	3 lbs.	J6006PBF	J6008RK	B107.14M
J6016C	1/2 Inch	30 ft. lbs.	150 ft. lbs.	1 ft. lbs.	21-1/2"	1-7/8"	1-13/32"	5 lbs.	J6014PBF	J6014RK	B107.14M
J6014C	1/2 Inch	50 ft. lbs.	250 ft. lbs.	1 ft. lbs.	27-1/8"	1-7/8"	1-13/32"	5.9 lbs.	J6014PBF	J6014RK	B107.14M
J6018AB	3/4 Inch	60 ft. lbs.	300 ft. lbs.	2 ft. lbs.	32-23/32"	2-5/8"	2-1/16"	14 lbs.	J6007PBF	J6018RK	B107.14M
J6020AB	3/4 Inch	120 ft. lbs.	600 ft. lbs.	2 ft. lbs.	41-9/16"	2-5/8"	2-1/16"	15.5 lbs.	J6007PBF	J6018RK	B107.14M
J6022B	1 Inch	140 ft. lbs.	700 ft. lbs.	2 ft. lbs.	46-27/32"	2-5/8"	2-5/16"	20.5 lbs.	J6007PBF	J6022RK	B107.14M

MICROMETER TORQUE WRENCH - RATCHETING HEAD

- Metric.
- Calibrated to +/- 3% clockwise direction and +/- 6% counter clockwise direction at 20% to 100% of full scale.
- Calibration is accomplished by manual loading the torque wrenches.
- Manufactured to meet standard industrial torque applications, general industry, heavy equipment, and maintenance.



Product ID No.	Drive Size	Torque Range			Head Length	Head Width	Head Depth	Weight lbs.	Storage Case	Ratchet Repair Kit	ASME Spec.
		Min.	Max.	Increments							
J6006NMC	3/8 Inch	16 Nm	80 Nm	.5 Nm	15-1/2"	1-7/16"	1-1/64"	3 lbs.	J6006PBF	J6006RK	B107.14M
J6006MC	3/8 Inch	16 Nm	80 Nm	.5 Nm	15-1/2"	1-7/16"	1-1/64"	3 lbs.	J6006PBF	J6006RK	B107.14M
J6016NMC	1/2 Inch	40 Nm	200 Nm	1 Nm	21-1/2"	1-7/8"	1-13/32"	5 lbs.	J6014PBF	J6014RK	B107.14M
J6014NMC	1/2 Inch	70 Nm	350 Nm	1 Nm	27-1/8"	1-7/8"	1-13/32"	5.9 lbs.	J6014PBF	J6014RK	B107.14M
J6014MC	1/2 Inch	70 Nm	350 Nm	1 Nm	27-1/8"	1-7/8"	1-13/32"	5.9 lbs.	J6014PBF	J6014RK	B107.14M
J6016MC	1/2 Inch	40 Nm	200 Nm	1 Nm	21-1/2"	1-7/8"	1-13/32"	5 lbs.	J6014PBF	J6014RK	B107.14M
J6020NM	3/4 Inch	120 Nm	800 Nm	4 Nm	41-9/16"	2-5/8"	2-1/16"	15.5 lbs.	J6007PBF	J6018RK	B107.14M