

Precision Torque



SET NO J5100 - 3/8" DRIVE 9 PC. TORQUE ADAPTER SET - 12 POINT

- Designed for easy torque calibrations.
- Adapters measure 2" from the center of the square drive to the center of the adapter opening.
- Special heat-treated alloy steel helps to increase strength and durability.
- Box end wall thickness is specially engineered to provide strength while still allowing ample room for access to reach difficult fasteners.
- Weight: 1.32 lbs.



Product		
ID No.	Contents	Description
J5100	J5112	Torque Adapter 3/8" drive 3/8"
	J5114	Torque Adapter 3/8" drive 7/16"
	J5116	Torque Adapter 3/8" drive 1/2"
	J5118	Torque Adapter 3/8" drive 9/16"
	J5120	Torque Adapter 3/8" drive 5/8"
	J5122	Torque Adapter 3/8" drive 11/16"
	J5124	Torque Adapter 3/8" drive 3/4"
	J5126	Torque Adapter 3/8" drive 13/16"
	J5128	Torque Adapter 3/8" drive 7/8"
J2599	Socket Bar for Torque Adapters	

3/8" DRIVE TORQUE ADAPTERS

- Designed for easy torque calibrations.
- Adapters measure 2" from the center of the square drive to the center of the adapter opening.
- Special heat-treated alloy steel helps to increase strength and durability.
- Box end wall thickness is specially engineered to provide strength while still allowing ample room for access to reach difficult fasteners.



Product					Weight	
ID No.	Size (In)	B	C	L	lbs.	AS Spec.
J5112	3/8"	9/16"	17/64"	2-11/16"	0.08 lbs.	AS954E S3.8.1
J5114	7/16"	21/32"	19/64"	2-47/64"	0.10 lbs.	AS954E S3.8.1
J5116	1/2"	47/64"	21/64"	2-25/32"	0.10 lbs.	AS954E S3.8.1
J5118	9/16"	13/16"	23/64"	2-13/16"	0.12 lbs.	AS954E S3.8.1
J5120	5/8"	29/32"	25/64"	2-55/64"	0.12 lbs.	AS954E S3.8.1
J5122	11/16"	1"	27/64"	2-29/32"	0.12 lbs.	AS954E S3.8.1
J5124	3/4"	1-5/64"	29/64"	2-61/64"	0.12 lbs.	AS954E S3.8.1
J5126	13/16"	1-11/64"	31/64"	2-63/64"	0.14 lbs.	AS954E S3.8.1
J5128	7/8"	1-17/64"	33/64"	3-1/32"	0.16 lbs.	AS954E S3.8.1

