## INDICATOR HOLDERS

## 657 INDICATOR HOLDERS

Base has three precision ground, magnetic contact surfaces. Grips horizontally, vertically or upside down. V-step holds base to round surfaces. Extra #1/4-20 tapped hole in one side of base (not shown) for mounting post.

Available with or without Starrett AGD Dial Indicators: inch reading 25-131J (graduation .0005", dial reading 0-25-0, range .125") or millimeter reading 25-181J (graduation 0.01mm, dial reading 0-50-0, range 2.5mm). Other indicators can be furnished on request.

657 Base Holder Assembly and Individual Components							
Photo Key	Description			Cat. No.	EDP		
	Magnetic Base, Upright Post Assembly Including Post, Swivel Post Snug and Gage Holding Rod			657D	52749		
А	Magnetic Base Only			657P	52757		
В	Upright Base Post Only			657G	52753		
С	Swivel Post Snug Only			657H	52785		
D	Gage Holding Rod with Clamp Mechanism			PT06784-A	52755		
E	Universal Snug with 5/16" and 3/8" Hole Dia.			57S	50296		
F	Universal Snug with 1/4", 5/16" and 3/8" Hole Dia.			58S	56613		
Sets Including Magnetic Base, Upright Post Assembly and AGD Dial Indicators							
		w/Finished Wood Case		Without Case			
Description		Cat. No.	EDP	Cat. No.	EDP		
Base and Upright Post Assembly with Inch Reading Indicator 25-131J		657EZ	52751	657E	52750		
Base and Upright Post Assembly with Millimeter Reading Indicator 25-181J		657MEZ	56358	657ME	56357		

- A. 657P Magnetic Base. 1-15/16" x 1-5/8" x 1-7/8" (50 x 40 x 48mm) deep. Push button on/off switch for one-hand operation.
- B. 657G Upright Base Post. 3/8" (9.5mm) diameter x 7-7/16" (190mm) length overall.
- C. 657H Swivel Post Snug. Allows universal indicator adjustment – up-and-down, any vertical angle, for a complete 360°. Two 3/8" (9.5mm) holes.
- D. PT06784-A Gage Holding Rod. 3/8" x 9-1/2" (9.5 x 240mm) with clamping mechanism for gripping the indicator lug back (see photo below).
- E. F. 57S and 58S Universal Snugs. Adapt various scribers and indicator shanks to rods and posts.



## INDICATOR HOLDERS

## 657/ MAGNETIC BASE INDICATOR HOLDER

For use with all Starrett Test, Back-Plunger, AGD, Dial and Miniature-Dial Indicators. Also accommodates similar indicators of other manufacturers.

- A. 657P Magnetic Base. 1-15/16 x 1-5/8 x 1-7/8" (50 x 40 x 48mm). Push-button on/off switch for one-hand operation. Base has three precision ground magnetic contact points. Grips horizontally, vertically, and upside down. V-step holds base to arbors, shafts, etc. Base has extra 1/4-20 tapped hole on one side for mounting post. Black wrinkle finish on non-working surfaces.
- B. 657G Upright Base Post. 3/8" (9.5mm) diameter x 7-7/16" (190mm) length overall. 57S and 58S Universal Snugs may also be used.
- C. 657S Snug. Two 1/4" (6.3mm) diameter holes. Adapts 196, 650, and 651 Dial Indicators and 657Y Indicator Attachment to 657X Rod.
- D. 657X Rod. 1/4" (6.3mm) diameter x 6" (150mm) long. Accommodates Starrett 708, 709, 811 and 711F Dial Test Indicators and 657S Sleeve.
- E. 657Y Indicator Attachment. 1/4" (6.3mm) O.D. one end, other end threaded and fits lug backs of all AGD indicators (81, 25, 655, 656) and 80 Miniature Indicators.
- F. PT18724 Snug. 3/8" (9.5mm) diameter post hole. 1/4" (6.3mm) diameter gripping hole accommodates 657X Rod.

ndividual Components

EDP

52757

52753

Cat. No.

657P

657G



657Y with lug-on-center back



657AA with 196B1 Universal Dial Indicator

D

B



65744	with	711EC	Loct We	ord® Dial	Toot	Indicator
UJIAA	VVILII	1110	Lasi VV	nu Diai	1621	inuicator

657AA Mag	netic Base Indicator Holder -
Photo Key	
A	Magnetic Base Only
В	7-7/16" Upright Base Post On
С	Snug with Two 1/4" (6.3 mm)

С	Snug with Two 1/4" (6.3 mm) Holes	657S	52759
D	Rod	657X	52764
E	Indicator Attachment	657Y	52765
F	Snug Complete – 1/4" and 3/8" Holes	PT18724	50710
657AA Magi	netic Base Indicator Holder - Comp	lete Set	
Description		Cat. No.	EDP
Magnetic Base with All Attachments – A, B, C, D, E, F		657AA	52743
Base and Post Assembly with 650B1 Indicator, 657S Snug, and 3 Contact Points		657-650Z	65259



Starrett

178