ELECTRONIC CALIPERS

799 ELECTRONIC CALIPERS

0-40"/0-1000MM



The 799 Electronic Caliper is light, comfortable, easy-to-use, and constructed with features that have made Starrett slide calipers the machinist's first choice for many years.

The 799 offers a slim, streamlined profile, a large, clear, easy-to-read LCD display, long battery life, and function buttons for zero and inch/ mm.

799 are available in 0-6", 0-8", and 0-12" sizes and the newly available extended range 24" and 40". All sizes furnished in a fitted, protective case.

FEATURES (ALL SIZES)

- Lightweight, ergonomic design
- Inch/millimeter conversion reads .0005" or 0.01mm
- Easy access to the single, long-life battery
- Last measuring position retained when shut off
- Hardened stainless steel body for long life
- Fine adjustment thumb wheel
- Lock screw to hold the slide in position
- Resolution is .0005" (0.01mm)
- · Zero at any position

799 Electronic Calipers					
Range	Cat. No.	EDP			
0-6" (150mm)	799A-6/150	67410			
	799A-6/150 W/SLC†	67620			
0-8" (200mm)	799A-8/200	67412			
	799A-8/200 W/SLC†	67413			
0-12" (300mm)	799A-12/300	67621			
0-24" (600mm)	799AZ-24/600	11978			
0-40" (1000mm)	799AZ-40/1000	11979			

Accessories and Case Information for 799 Electronic Calipers					
Description	Cat. No.	EDP			
Center distance attachment*	PT26151	64440			
Depth attachment for 6", 9" and 150mm calipers	PT22431	64640			
3 Volt battery; CR2032	PT99492	65650			
Deluxe padded case for 0-6" (150mm) calipers	723ZZ-6/722ZZ-6	57070			
Finished wood case for 0-8" (200mm) calipers	950	63878			
Finished wood case for 0-12" (300mm) calipers	946	56695			

^{*} See details in this section.

†Includes redemption card for Standard Letter of Certification (SLC).

	Approximate Jaw Depths for 799 Electronic Calipers				
	6"	8"	12"	24"	40"
	(150mm)	(200mm)	(300mm)	(600mm)	(1000mm)
Outside	1-1/2"	2"	2-1/2"	4"	6"
	(38mm)	50.8mm)	(63.5mm)	(100mm)	(150mm)
Inside	5/8"	3/4"	23/32"	11/16"	11/16"
	(16mm)	(19mm)	(18.3mm)	(17.46mm)	(17.46mm)

6". 8" AND 12" CALIPERS ONLY

- Large easy-to-read LCD, .32" high characters
- Automatic shut-off after 5 minutes of nonuse
- Linear accuracy meets DIN862
- Integrated depth rod

EXTENDED RANGE 24" AND 40" CALIPERS

- Preset and hold feature
- Minimum and maximum limits set
- I.D. jaw dimension is 0.800"/20.32mm
- LCD characters are .50" high
- · Auto shut-off after 30 minutes of non-use







BASIC ELECTRONIC TOOL SETS

S766∧

WITHOUT OUTPUT

Basic starter sets for electronic measuring include slide calipers and 1"/25mm micrometers. Two sets without output are offered: S766AZ for English units and S766MAZ for metric. Both sets include an attractive, protective case.





S766B

WITH OUTPUT AND IP PROTECTION

Basic starter sets for electronic measuring with output capability for SPC, and IP protection against dirt, dust, water and coolant.

They include the 798B-6/150 Slide Calipers with IP65 protection and output, and the 795XFL-1 or 795MEXFL-25 1"/25mm micrometers with IP67 protection and output.

Two sets are offered - sets S766BZ and S766MBZ. Both sets include an attractive, protective case.

S766AZ/EDP 12206 - Inch Set (without output)			
Cat. No.	Description		
799A-6/150	0-6" (0-150mm) electronic slide caliper		
3732XFL-1	0-1" (0-25mm) electronic outside micrometer		
S766MAZ/EDP 12207 - Millimeter Set (without output)			
Cat. No.	Description		
799A-6/150	0-6" (0-150mm) Electronic Slide Caliper		
3732MEXFL-25	0-1" (0-25mm) Electronic Outside Micrometer		
S766BZ/EDP 11606 - Inch Set (with output)			
Cat. No.	Description		
798B-6/150	0-6" (0-150mm) Electronic Slide Caliper with output		
795XFL-1	0-1" (0-25mm) Electronic Outside Micrometer with output		
S766MBZ/EDP 11607 - Millimeter Set (with output)			
Cat. No.	Description		
798B-6/150	0-6" (0-150mm) Electronic Slide Caliper with output		
795MEXFL-25	0-1" (0-25mm) Electronic Outside Micrometer with output		



