

ULTRA Glass LED A-line Lamps

25,000 Hour Life



SYLVANIA offers an extensive portfolio of Classic LED A-line lamps. All lamps have the look and feel of traditional incandescent lamps, while utilizing all the benefits and innovation of LEDs, such as energy savings, long life, and brilliant illumination, while promoting job growth and supporting the U.S. economy.

Assembled in USA ULTRA LED A-line lamps are direct replacements for 40/60/75/100W incandescent lamps and are available in a warm white 2700K and a cool white 5000K.

All lamps are dimmable, have an excellent color rendering of 80+, and are rated up to 25,000 hours (L₇₀) of life. They are also ENERGY STAR certified for increased utility rebates, making them ideal for a variety of residential and commercial applications.

Key Features & Benefits

- Lamps Assembled in the USA
- Full glass housing manufactured in the USA
- Look and feel of traditional lamps while utilizing all the benefits of LEDs
- Available in 2700K and 5000K color temperatures
- Indoor and outdoor rated (UL Damp)
- Mercury and lead free
- Dimmable
- ENERGY STAR® certified
- Long rated life of 25,000 hours (L₇₀)
- No warm up time, instant on with full light output and stable color



Product Offering

Ordering Abbreviation	Wattage	Color Temperature	Typical Lumens
LED4.5A19	4.5	2700K, 5000K	450
LED6.519	6.5	2700K, 5000K	800
LED9A21	9	2700K, 5000K	1100
LED11A21	11	2700K, 5000K	1600

Application Information

Applications

- Downlights
- Pendant fixtures
- Table/floor lamps
- Wall sconces

Market Segments

- Hospitality
- Office
- Residential
- Retail

Application Notes

1. Operating temperature range between -20°C and +45°C (-4°F and +113°F)
2. Not for use with emergency light fixtures or exit lights
3. Suitable for damp locations



Specification Data

Catalog #	Type
Project	
Comments	
Prepared by	

Ordering Information


Item Number	Ordering Abbreviation	Wattage (W)	Base Type	Replaces	Input Voltage (V)	Average Rated Life (hrs.)	CCT	Typical Lumens (lm)	CRI	Bulb Finish	ENERGY STAR®
74963	LED4.5A19/DIM/O/827/RP4	4.5	Medium	40W	120	25,000	2700K	450	82	Frosted	Yes
74964	LED4.5A19/DIM/O/827/RP	4.5	Medium	40W	120	25,000	2700K	450	82	Frosted	Yes
74965	LED4.5A19/DIM/O/850/RP4	4.5	Medium	40W	120	25,000	5000K	450	82	Frosted	Yes
74966	LED4.5A19/DIM/O/850/RP	4.5	Medium	40W	120	25,000	5000K	450	82	Frosted	Yes
74967	LED6.5A19/DIM/O/827/RP4	6.5	Medium	60W	120	25,000	2700K	800	82	Frosted	Yes
74968	LED6.5A19/DIM/O/827/RP	6.5	Medium	60W	120	25,000	2700K	800	82	Frosted	Yes
74969	LED6.5A19/DIM/O/850/RP4	6.5	Medium	60W	120	25,000	5000K	800	82	Frosted	Yes
74970	LED6.5A19/DIM/O/850/RP	6.5	Medium	60W	120	25,000	5000K	800	82	Frosted	Yes
74971	LED9A21/DIM/O/827/RP4	9	Medium	75W	120	25,000	2700K	1100	82	Frosted	Yes
74972	LED9A21/DIM/O/827/RP	9	Medium	75W	120	25,000	2700K	1100	82	Frosted	Yes
74973	LED9A21/DIM/O/850/RP4	9	Medium	75W	120	25,000	5000K	1100	82	Frosted	Yes
74974	LED9A21/DIM/O/850/RP	9	Medium	75W	120	25,000	5000K	1100	82	Frosted	Yes
74975	LED11A21/DIM/O/827/RP4	11	Medium	100W	120	25,000	2700K	1600	82	Frosted	Yes
74976	LED11A21/DIM/O/827/RP	11	Medium	100W	120	25,000	2700K	1600	82	Frosted	Yes
74977	LED11A21/DIM/O/850/RP4	11	Medium	100W	120	25,000	5000K	1600	82	Frosted	Yes
74978	LED11A21/DIM/O/850/RP	11	Medium	100W	120	25,000	5000K	1600	82	Frosted	Yes

Ordering Guide

LED	4.5	A19	/	DIM	/	O	/	8	27	/	RP4
LED	Wattage	Lamp Type		Dimmable		Omnidirectional		CRI	CCT		Retail Pack

Lamp Dimensions

	(A) MOL inches (mm)	(B) Diameter inches (mm)
LED4.5A19	4.4 (112)	2.36 (60)
LED6.5A19	4.4 (112)	2.36 (60)
LED9A21	5.17 (131.4)	2.56 (65)
LED11A21	5.17 (131.4)	2.56 (65)



LEDVANCE LLC
 200 Ballardvale Street
 Wilmington, MA 01887 USA
 Phone 1-800-LIGHTBULB (1-800-544-4828)
www.sylvania.com

SYLVANIA and LEDVANCE are registered trademarks.
 All other trademarks are those of their respective owners.
 Licensee of product trademark SYLVANIA in general lighting.
 Specifications subject to change without notice.

[/sylvania](https://www.facebook.com/sylvania) [/sylvania](https://www.facebook.com/sylvania)

