# Desk Consoles

## Application -

Intended for indoor use to provide a degree of protection to personnel against access to hazardous parts, also to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects and falling dirt, to provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water, splashing water. Designed for use in a standing or sitting position with single and dual access and top that opens for easy accessibility. For installation information, consult our Installation Manual at www.saginawcontrol. com.

### **Construction -**

- · 0.075" carbon steel.
- Seams continuously welded and ground smooth.
- · 25 degree Sloped top.
- Door props on sloped door to hold in the open position.
- · Oil and water resistant gasket.
- Flange trough collar around all sides of door opening.
- · Concealed hinges.
- Removable doors.
- · Removable print pocket.
- · Ground studs on door and body.
- Rubber pads with provision for leveling pads on bottom of enclosure.
- Black quarter turn latches on top door.
- Keylocking black 3-point flush swing handle in front door of single access, front and rear doors on dual access.
- Mounting studs welded on interior back for mounting optional sub-panels on single access console
- Mounting channels welded on sides of interior body for mounting optional sub-panels on dual access console.
- Mounting hardware included for (1) optional subpanel.

## Finish -

ANSI-61 gray powder coated inside and out. Optional sub-panels powder coated white.

#### Options -

Optional tamper-resistant inserts or padlocking handles are available.

#### IS3 - Industry Standards -

NEMA Type 3R, 12 & Type 13 UL Listed Type 3R & 12 CSA Type 3R & 12 IEC 60529 IP55

## IS4 - Industry Standards -

NEMA Type 3R, 4, 12 & Type 13 UL Listed Type 3R, 4 & 12 CSA Type 3R, 4 & 12 IEC 60529 IP66

\*\*\*Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

## **DESK CONSOLES**

ENCL	SUB-PANEL (P3)								
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standar		Catalog No.	Panel Height (D)	Panel Width (E)	List Price
Single Access Single-Door									
SCE-402516SDC	40.25	25.25	15.50	IS4	942.59	SCE-30P24	27.00	21.00	63.29
SCE-403716SDC	40.25	37.25	15.50	IS3	1,071.39	SCE-36P30	33.00	27.00	101.27
SCE-462519SDC	46.25	25.25	18.50	IS4	1,298.64	SCE-36P24	33.00	21.00	75.96
SCE-463719SDC	46.25	37.25	18.50	IS3	1,441.43	SCE-36P36	33.00	33.00	118.99
Dual Access Sing									
SCE-462519DC	46.25	25.25	18.50	IS4	1,383.50	SCE-36P24	33.00	21.00	75.96
SCE-463719DC	46.25	37.25	18.50	IS3	1,522.45	SCE-36P36	33.00	33.00	118.99
Single Access Ov									
SCE-464919SDC	46.25	49.25	18.50	IS3	1,667.18	SCE-48P36	45.00	33.00	154.46
SCE-466019SDC	46.25	59.88	18.50	IS3	2,158.34	SCE-60PC36	55.63	33.00	181.41
<b>Dual Access Ove</b>	rlapping T	wo-Door							
SCE-464919DC	46.25	49.25	18.50	IS3	1,753.31	SCE-48P36	45.00	33.00	154.46
SCE-466019DC	46.25	59.88	18.50	IS3	2,330.54	SCE-60PC36	55.63	33.00	181.41
<b>Dual Access Two</b>									
SCE-464919DCC	46.25	49.25	18.50	IS4	2,061.51	SCE-48P36	45.00	33.00	154.46
SCE-466019DCC	46.25	59.88	18.50	IS4	2,648.34	SCE-60PC36	55.63	33.00	181.41





Phone (989) 799-6871 Fax (989) 799-4524

