

## THREE-DOOR ENCLOSURES

ENCLOSURE PRODUCT CODE A2						SUB-PANEL (P3)			
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	List Price	Catalog No.	Panel Height (D)	Panel Width (E)	List Price
SCE-72XD3EQ18	72.00	99.50	18.00	IS3	5,563.84	SCE-64P31** & SCE-64P64**	60.00	27.75	Included
SCE-72XD3EQ18G	72.00	99.50	18.00	IS3	5,698.50	SCE-64P31GALV** & SCE-64P64GALV**	60.00	27.75	Included
SCE-72XD3EW18	72.00	117.50	18.00	IS3	6,112.02	SCE-76P37** & SCE-64P76**	72.00	33.75	Included
SCE-72XD3EW18G	72.00	117.50	18.00	IS3	6,267.77	SCE-76P37GALV** & SCE-64P76GALV**	72.00	33.75	Included
SCE-84XD3EW18	84.00	117.50	18.00	IS3	6,676.66	SCE-76P37** & SCE-76P76**	72.00	33.75	Included
SCE-84XD3EW18G	84.00	117.50	18.00	IS3	6,865.73	SCE-76P37GALV** & SCE-76P76GALV**	72.00	33.75	Included



## XD Heavy Duty Free-Standing Enclosures with External Disconnect Enclosure Installed

### Application -

Designed to house the main power supply in external enclosure on the right side of main enclosure, keeping the live side of the power supply separate from the primary electrical equipment. Provides protection from dirt, dust, oil and water and can house most standard type disconnects. For Installation information consult our Installation Manual at [www.saginawcontrol.com](http://www.saginawcontrol.com).

### Construction -

- 0.125" carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Body stiffeners in large enclosures for extra rigidity.
- Heavy duty lifting eyes anchor into reinforced top.
- Removable center posts permit easy sub-panel installation.
- Concealed hinges.
- Black zinc die cast padlocking handles.
- 3-point latching mechanism.
- Large removable print pockets.
- Oil-resistant gasket.
- Removable panels mount on collar studs.
- Defeater on master door requires a screwdriver to open.
- Mechanical interlock activated by the External Disconnect prevents main door of the enclosure from being closed unless the EXD enclosure is first closed.
- Mechanical interlock activated by master door prevents slave doors from being opened first. Doors can be closed in any order.
- Hole plugs provided to seal holes in bottom of enclosure.
- Ground stud on door and body.
- Provisions for light kit.

**Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure.**

### Finish -

ANSI-61 gray powder coated inside and out. Sub-panels powder coated white.

### IS3 - Industry Standards -

NEMA Type 3R, 12 & Type 13  
UL Listed Type 3R & 12  
CSA Type 3R & 12  
IEC 60529 IP55

### IS4 - Industry Standards -

NEMA Type 3R, 4, 12 & Type 13  
UL Listed Type 3R, 4 & 12  
CSA Type 3R, 4 & 12  
IEC 60529 IP66

\*\*\*Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.