258

Stainless Steel
Enviroline® Series
Wall-Mount Two-Door
Enclosures With
3-Point Hardware

Application -

Designed to house electrical and electronic controls, instrumentation and components. For outdoor applications a drip shield is recommended. For installation information, consult our Installation Manual at www. saginawcontrol.com.

Construction -

- 0.075" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Collar studs provided for mounting optional sub-panels.
- Removable center posts permit easy sub-panel installation.
- Mounting holes in back of the enclosure for wall mounting.
- Mounting hardware, sealing washers and hole plugs included.
- · Stainless steel concealed hinges.
- · Removable and interchangeable doors.
- · Black keylocking padlocking handles.
- · 3-point latching mechanism.
- · Removable print pocket.
- · Oil & water resistant gasket.
- · Ground stud on door and body.

Options -

Provisions for mechanical interlock. See accessory section to order.

Finish -

#4 Brushed finish on all exterior surfaces. Optional sub-panels powder coated white.

Notes

Mechanical Interlock not for use in Enclosures 24" in height.

IS6 - Industry Standards -

NEMA Type 3R, 4, 4X, 12 & Type 13 UL Listed Type 3R, 4, 4X & 12 CSA Type 3R, 4, 4X & 12 IEC 60529 IP66

***Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

STAINLESS STEEL ENVIROLINE® SERIES WALL-MOUNT TWO-DOOR ENCLOSURES WITH 3-POINT HARDWARE

ENCLOS	SUB-PANEL (P3)								
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standar		Catalog No. H	Panel eight (E)	Panel Width (F)	List Price
SCE-24EL4210SSWFLP	24.00	42.00	10.00	IS6 2	2,990.12	SCE-42P24	24.00	42.00	2,990.12
SCE-24EL4810SSWFLP	24.00	48.00	10.00	IS6	3,108.66	SCE-48P24	24.00	48.00	3,108.66
SCE-30EL4210SSWFLP	30.00	42.00	10.00	IS6	3,168.28	SCE-42P30	30.00	42.00	3,168.28
SCE-30EL4810SSWFLP	30.00	48.00	10.00	IS6	3,347.42	SCE-48P30	30.00	48.00	3,347.42
SCE-30EL6010SSWFLP	30.00	60.00	10.00	IS6	3,758.21	SCE-60P30	30.00	60.00	3,758.21
SCE-36EL4212SSWFLP	36.00	42.00	12.00	IS6	3,772.54	SCE-42P36	36.00	42.00	3,772.54
SCE-36EL4812SSWFLP	36.00	48.00	12.00	IS6	3,866.89	SCE-48P36	36.00	48.00	3,866.89
SCE-36EL6012SSWFLP	36.00	60.00	12.00	IS6 4	4,269.15	SCE-60P36	36.00	60.00	4,269.15
SCE-42EL4212SSWFLP	42.00	42.00	12.00	IS6	3,824.34	SCE-42P42	42.00	42.00	3,824.34
SCE-42EL4812SSWFLP	42.00	48.00	12.00	IS6 4	4,248.08	SCE-48P42	42.00	48.00	4,248.08
SCE-42EL6012SSWFAL	P 42.00	60.00	12.00	IS6 4	4,460.85	SCE-60BFP4	2 48.00	48.00	4,359.04
SCE-48EL4812SSWFLP	48.00	48.00	12.00	IS6	4,359.04	SCE-48P48	20.00	21.38	909.44





