

## Stainless Steel Enviroline® Series Wall-Mount Sloping Top Disconnect Enclosures

### Application -

Designed to house most standard type disconnects. For installation information, consult our Installation Manual at [www.saginawcontrol.com](http://www.saginawcontrol.com).

### Construction -

- 0.075" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- 15 Degree Sloping Top.
- Stainless steel concealed hinges.
- Stainless steel coinproof/padlocking handle.
- 3-point latching mechanism.
- Removable print pocket on main door of disconnect enclosures.
- Oil & water resistant gasket.
- Mounting hardware, sealing washers and hole plugs included.
- Black quarter turn latches as required.
- Ground stud on door and body.

**Disconnect switch (or circuit breaker) and operating mechanism are not furnished with this enclosure.**

### Finish -

# 4 Brushed finish on all exterior surfaces.  
Optional sub-panels powder coated white.

### Options -

Wall-Mount Standoffs available under Mounting Options in the Accessories Section.

### IS6 - Industry Standards -

NEMA Type 3R, 4, 4X, 12 & Type 13  
UL Listed Type 3R, 4, 4X & 12  
CSA Type 3R, 4, 4X & 12  
IEC 60529 IP66

\*\*\*Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

## STAINLESS STEEL ENVIROLINE® SERIES WALL-MOUNT SLOPING TOP DISCONNECT ENCLOSURES

ENCLOSURE PRODUCT CODE S8						SUB-PANEL (P3)			
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	List Price	Catalog No.	Panel Height (E)	Panel Width (F)	List Price
SCE-24XEL2510SSST	24.00	25.38	10.00	IS6	1,555.73	SCE-24P24	21.00	21.00	53.18
SCE-30XEL2510SSST	30.00	25.38	10.00	IS6	1,759.14	SCE-30P24	27.00	21.00	63.29
SCE-36XEL3110SSST	36.00	31.38	10.00	IS6	1,968.03	SCE-36P30	33.00	27.00	101.27
SCE-48XEL3712SSST	48.00	37.38	12.00	IS5	3,788.29	SCE-48P36	45.00	33.00	154.46
SCE-48XEL3716SSST	48.00	37.38	16.00	IS6	3,637.40	SCE-48P36	45.00	33.00	154.46
SCE-60XEL3716SSST	60.00	37.38	16.00	IS6	4,467.49	SCE-60P36	57.00	33.00	189.89



Phone (989) 799-6871  
Fax (989) 799-4524

