

Stainless Steel Enviroline® Series Two-Door Sloping Top Enclosures

Application -

Designed to house electrical and electronic controls, instrumentation and components in indoor, outdoor and sanitary locations. For Installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction -

- 0.104" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- 15 Degree Sloping Top.
- Removable center post.
- Heavy duty lifting eyes anchor into reinforced top.
- Body stiffeners.
- Black quarter turn latches as required.
- Stainless steel concealed hinges.
- Stainless steel padlocking handles.
- 3-point latching mechanism.
- Removable print pocket.
- Provisions for floor stands.
- Panel supports.
- Oil & water resistant gasket.
- Ground stud on door and body.
- Provisions for light kit.

Finish -

#4 brushed finish on all exterior surfaces.
Optional sub-panels powder coated white.

IS6 - Industry Standards -

NEMA Type 3R, 4, 4X, 12 & Type 13
UL Listed Type 3R, 4, 4X & 12
CSA Type 3R, 4, 4X & 12
IEC 60529 IP66

***Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

STAINLESS STEEL ENVIROLINE® SERIES TWO-DOOR SLOPING TOP ENCLOSURES

ENCLOSURE PRODUCT CODE S8						SUB-PANEL (P3)			
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	List Price	Catalog No.	Panel Height (E)	Panel Width (F)	List Price
SCE-60EL4812SSST	60.00	48.00	12.00	IS6	9,739.09	SCE-60P48	56.00	44.00	268.38
SCE-60EL4818SSST	60.00	48.00	18.00	IS6	10,330.10	SCE-60P48	56.00	44.00	268.38
SCE-60EL6012SSST	60.00	60.00	12.00	IS6	10,930.58	SCE-60P60	56.00	56.00	331.68
SCE-60EL6018SSST	60.00	60.00	18.00	IS6	11,447.45	SCE-60P60	56.00	56.00	331.68
SCE-72EL6012SSST	72.00	60.00	12.00	IS6	12,466.03	SCE-72P60	68.00	56.00	394.98
SCE-72EL6018SSST	72.00	60.00	18.00	IS6	12,732.08	SCE-72P60	68.00	56.00	394.98
SCE-72EL7212SSST	72.00	72.00	12.00	IS6	13,461.80	SCE-72P72	68.00	68.00	470.93
SCE-72EL7218SSST	72.00	72.00	18.00	IS6	14,468.96	SCE-72P72	68.00	68.00	470.93
SCE-72EL7224SSST	72.00	72.00	24.00	IS6	14,982.80	SCE-72P72	68.00	68.00	470.93



Phone (989) 799-6871
Fax (989) 799-4524

