

Stainless Steel EnviroLine® Series Two-Door Sloping Top Disconnect Enclosures

Application -

Designed to house most standard type disconnects. For installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction -

- 0.104" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- 15 Degree Sloping Top.
- Removable center post.
- Heavy duty lifting eyes anchor into reinforced top.
- Body stiffeners.
- Stainless steel concealed hinges.
- Mechanical interlock.
- Stainless steel coinproof/padlocking handle on main door with stainless steel padlocking handle on slave doors.
- 3-point latching mechanism.
- Black quarter turn latches as required.
- Removable print pocket on main door of disconnect enclosures.
- Provisions for floor stands.
- Panel supports.
- Oil & water resistant gasket.
- Ground stud on door and body.
- Provisions for light kit.

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with this enclosure.

Finish -

#4 brushed finish on all exterior surfaces.
Optional sub-panels powder coated white.

IS6 - Industry Standards -

NEMA Type 3R, 4, 4X, 12 & Type 13
UL Listed Type 3R, 4, 4X & 12
CSA Type 3R, 4, 4X & 12
IEC 60529 IP66

***Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

STAINLESS STEEL ENVIROLINE® SERIES TWO-DOOR SLOPING TOP DISCONNECT ENCLOSURES

ENCLOSURE PRODUCT CODE S8						SUB-PANEL (P3)			
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	List Price	Catalog No.	Panel Height (E)	Panel Width (F)	List Price
SCE-60XEL4912SSST	60.00	49.00	12.00	IS6	10,930.50	SCE-60P48	56.00	44.00	268.38
SCE-60XEL4918SSST	60.00	49.00	18.00	IS6	11,907.20	SCE-60P48	56.00	44.00	268.38
SCE-60XEL6112SSST	60.00	61.00	12.00	IS6	12,222.40	SCE-60P60	56.00	56.00	331.68
SCE-60XEL6118SSST	60.00	61.00	18.00	IS6	13,310.84	SCE-60P60	56.00	56.00	331.68
SCE-72XEL6112SSST	72.00	61.00	12.00	IS6	13,538.08	SCE-72P60	68.00	56.00	394.98
SCE-72XEL6118SSST	72.00	61.00	18.00	IS6	14,707.18	SCE-72P60	68.00	56.00	394.98
SCE-72XEL7312SSST	72.00	73.00	12.00	IS6	15,037.00	SCE-72P72	68.00	68.00	470.93
SCE-72XEL7318SSST	72.00	73.00	18.00	IS6	15,621.61	SCE-72P72	68.00	68.00	470.93
SCE-72XEL7324SSST	72.00	73.00	24.00	IS6	16,334.37	SCE-72P72	68.00	68.00	470.93



Phone (989) 799-6871
Fax (989) 799-4524

