Stainless Steel Heavy **Duty Free-Standing Enclosures For** Flange-Mounted **Disconnects**

Application -

Designed to house electrical equipment and provide degree of protection from dirt, dust, oil and water and to house most standard type disconnects. For installation information, consult our Installation Manual at www. saginawcontrol.com.

Construction -

- 0.104" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Body stiffeners in large enclosures for extra rigidity.
- Heavy duty lifting eyes anchor into reinforced top.
- Removable center posts permit easy sub-• panel installation.
- •
- Stainless steel concealed hinges. Black zinc die cast coinproof/padlocking • handle on main door with black zinc die cast padlocking handle on slave doors.
- 3-point latching mechanism. ٠
- Black quarter turn latches as required.
- Panel supports. •
- Large removable print pockets. •
- Oil-resistant gasket.
- Removable sub-panels mount on collar studs.
- Master door is far right-hand door on all enclosures.
- Defeater on master door requires a screwdriver to open.
- Mechanical interlock activated by master • door prevents slave doors from being opened first. Doors can be closed in any order.
- · Ground stud on door and body.
- Provisions for light kit.

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure.

Finish -

#4 brushed finish on all exterior surfaces. Sub-panels powder coated white.

IS6 - Industry Standards -

NEMA Type 3R, 4, 4X, 12 & Type 13 UL Listed Type 3R, 4, 4X & 12 CSA Type 3R, 4, 4X & 12 IEC 60529 IP66


***Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

STAINLESS STEEL HEAVY DUTY FREE-STANDING ENCLOSURES FOR FLANGE-MOUNTED DISCONNECTS

THREE-DOOR ENCLOSURES

ENCLOSURE PRODUCT CODE S2						SUB-PANEL (P3)			
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	List Price	Catalog No. He	Panel eight (E)	Panel Width (F)	List Price
SCE-72XM3EQ18SS	72.00	99.50	18.00	IS6 14,	816.33	SCE-64P31**	60.00	27.75	Included
						SCE-64P64**	60.00	60.00	Included
SCE-72XM3EW18SS	72.00	117.50	18.00	IS6 16,	677.48	SCE-64P37**	60.00	33.75	Included
						SCE-64P76**	60.00	72.00	Included
SCE-84XM3EW18SS	84.00	117.50	18.00	IS6 18,	594.54	SCE-76P37**	72.00	33.75	Included
						SCE-76P76**	72.00	72.00	Included
SCE-84XM3EW24SS	84.00	117.50	24.00	IS6 18,	813.76	SCE-76P37**	72.00	33.75	Included
						SCE-76P76**	72.00	72.00	Included
SCE-90XM3EW24SS	90.00	117.50	24.00	IS6 20,	748.01	SCE-82P37**	78.00	33.75	Included
						SCE-82P76**	78.00	72.00	Included

**Sub-panel included with enclosure. Replacement panels can be ordered. Prices found in the accessory section.





Phone (989) 799-6871 Fax (989) 799-4524



Operator oysterin Enclosures (Stainless Steel)