

## T150L9X2



Article Number: 111-15419

Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg



### Base Data

Local Order Number T150L9X2

Type T150L

Color Natural (NA)

- Features and Benefits**
- Heavy duty design to offer higher tensile strength.
  - Head design provides high tensile strength with very low insertion force.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg

### Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 32.3 "

Length L (metric) 820.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.8 mm

Bundle Diameter min (imperial) 0.32 "

Bundle Diameter min (metric) 8.0 mm

Bundle Diameter max (imperial) 9.6 "

Bundle Diameter max (metric) 245.0 mm

Thickness T (imperial) 0.079 "

Thickness T (Metric) 2 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 500

Weight (Metric) 16 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	MIL 53421 UL ZODZ2.E64139
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes