



# T5633-W

5.1A USB Type A/Type-C Wall Outlet Charger with 15A Tamper-Resistant Outlet

15 Amp, 125 Volt, Decora Tamper-Resistant Outlet. NEMA 5-15R, 25+W (5.1 Amp), Type A and Type-C USB In Wall Charger, Grounding, Side Wired & Back Wired - White

- SMART Built-in smart chip recognizes the individual device's charging requirements to optimize the charge (Does not provide Power Delivery. See Leviton T5635)
- POWERFUL Two high-powered charging ports deliver a combined total of 5.1A charging current and 25+ watts of power
- CONVENIENT No more searching for charging adapters! Upgrade so you can charge electronics leaving the outlets free for additional power needs
- THE FUTURE OF CHARGING USB Type-C provides faster charging and is emerging as the standard port on many phones, tablets and laptops
- ENHANCED SAFETY Built-in overcurrent protection helps protect electronics from receiving too much power, which can damage the device

# **Technical Information**

Product Features Amperage : 15 A Brand : Decora Color : White Flammability : Rated V-0 per UL 94 Grade : Residential/Commercial Specification Grade NEMA : 5-15R Operating Temperature : -10°C to 40°C Product Type : Outlet/USB Combo Type : Type A/C Duplex Receptacle Voltage : 125 VAC Wallplate : Not Included

**Electrical Specifications** 

Amperage : 15 ABody Material : ThermoplasticColor : WhiteCover Material : ThermoplasticGrounding : GroundingHorsepower Rating : 15A-1/2 HPRatings : 15A-125VStrap Material : SteelVoltage : 125 VAC

Environmental Specifications Flammability : Rated V-0 per UL 94 Operating Temperature : -10°C to 40°C Product ID : Stamped on Strap Terminal Accom. : 14-12 AWG Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd Termination : Back & Side Torgue Range : 14 – 18 in.-Ibs

Material Specifications

Body Material : Thermoplastic Color : White

Cover Material : Thermoplastic Grade : Residential/Commercial Specification Grade Strap Material : Steel

Mechanical Specifications Listed : cCSAus NOM : 057 Product ID : Stamped on Strap Terminal Accom. : 14-12 AWG Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd Termination : Back & Side

Torque Range : 14 – 18 in.-lbs Warranty : 2-Year Limited

Standards & Certifications

FCC Part 15 : Class B Listed : cCSAus NOM : 057 UL 1310 : Yes UL 498 : Yes Warranty : 2-Year Limited

## **Features and Benefits**

- Ideal for residential and commercial applications including kitchens, bedrooms, home offices, college dormitories, airport lounges, hospitals, salons and spas, hotels, meeting rooms, cafes, restaurants and more
- Smart chip technology recognizes and optimizes the charging requirements of individual devices including Apple, Samsung, Nexus, Pixel and more
- One Type A Port and one Type-C Port; combined total of 5.1A of charging power
- Type-C Port can charge maximum 3 Amps @ 5V
- Type A Port can charge maximum 2.4 Amps @ 5V
- Tamper-Resistant improves child safety built-in shutter prevents access by most non-rated/foreign objects
- USB Ports tested to withstand over 10,000 insertions
- Charges most Type A and Type-C USB powered devices
- Type-C Port permits the cables to be inserted easily in either direction
- Charging time may be affected by the charge cord used. Leviton recommends using the cord provided with the device
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates
- Compatible with USB 3.1, 3.0, 2.0, 1.1 devices
- No data transfer capability
- Compatible with Decora® wallplates and Decora Plus<sup>™</sup> screwless wallplates. Wallplate sold separately

# SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

## Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

#### Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

