


Cable Tie Mounting Bases

Choose from adhesive-backed, epoxy or screw mounting bases!

- Available in a variety of materials for both indoor and outdoor use
- One-piece molding — no lost parts
- Adhesive-backed with pressure-sensitive adhesive tape (where applicable)

Temperature Rating:
32°F to 150°F (0°C to 66°C)
*Synthetic Rubber Adhesive



Std. Pkg. Cat. No.	Bulk Pkg. Cat. No.	Mounting Method	Max. Tie Width Accom.	Length		Width		Material	Std. Pkg.	Bulk Pkg.
				(in.)	(mm)	(in.)	(mm)			
Two-Way Adhesive Mounting Bases										
TC5342A	TC342A	SRA* Adhesive	0.19	1.13	28.58	1.13	28.58	Nylon 6.6	100	1,000
-	TC342A-X							Weatherable Nylon		
-	TC342	TC2PA						Nylon 6.6		
-	TC342X							Weatherable Nylon		
-	TC342A-FR	SRA* Adhesive						Flame-Retardant Nylon		
-	TC342AH-TFR	Acrylic Adhesive						Black High-Temp Flame-Retardant Nylon		

Select the Four-way configuration you need!

- Eliminates errors in premounting the base with respect to its orientation to wire bundle direction
- Convenient way to mount wire bundles at cross-over points — two optional mounting holes included

Temperature Rating:
32°F to 150°F (0°C to 66°C)
*Synthetic Rubber Adhesive



Std. Pkg. Cat. No.	Bulk Pkg. Cat. No.	Mounting Method	Max. Tie Width Accom.	Length		Width		Material	Std. Pkg.	Bulk Pkg.
				(in.)	(mm)	(in.)	(mm)			
4-Way Adhesive Mounting Base										
TC5345A	TC345A	SRA* Adhesive	0.19	1.13	28.58	1.13	28.58	Nylon 6.6	100	1,000
-	TC345AFR							Flame-Retardant Nylon		
TC5345AX	TC345AX	Weatherable Nylon								
TC5345AHTFR	TC345AHTFR	Acrylic Adhesive						Black High-Temp Flame-Retardant Nylon		
-	TC345	TC2PA/Screws						Nylon 6.6		
-	TC345	TC2PA/Screws						Nylon 6.6		
4-Way Mini Base										
TC050X050A-C	TC050X050A	SRA* Adhesive	0.10	0.5	12.70	0.5	12.70	Nylon 6.6	100	1,000
TC050X050-C	TC050X050AX							Weatherable Nylon		
TC5344A	TC344A							Nylon 6.6		
TC5344AX	TC344AX	Weatherable Nylon								
TC5344	TC344	Screw Mount	Nylon 6.6							
Large 4-Way Base										
TC150X150L	TC150X150	Screw Mount	0.19	1.5	38.10	1.5	38.10	Nylon 6.6	50	500
TC150X150A-L	TC150150A	SRA* Adhesive						Weatherable Nylon		
TC150X150AX-L	TC150X150AX	Screw Mount	0.30	2.0	50.80	2.0	50.80	Nylon 6.6	-	-
TC200X200-L	TC200X200	SRA* Adhesive						Weatherable Nylon		
TC200X200A-L	TC200X200A	SRA* Adhesive	0.75	2.0	50.80	2.0	50.80	Nylon 6.6	-	-
-	TC200X200AX							Weatherable Nylon		
-	TC368	Screw Mount	0.75	2.0	50.80	2.0	50.80	Nylon 6.6	-	-
-	TC368A	SRA* Adhesive						Weatherable Nylon		

Great versatility!

- Accommodates the entire line of standard cable ties
- 4-way base for cable ties up to .184" maximum width and a two-way base for ties up to .301" maximum width
- It may also be mounted with #8 size screw (2 holes)

Temperature Rating:
32°F to 150°F (0°C to 66°C)
*Synthetic Rubber Adhesive



Std. Pkg. Cat. No.	Bulk Pkg. Cat. No.	Mounting Method	Max. Tie Width Accom.	Length		Width		Material	Std. Pkg.	Bulk Pkg.
				(in.)	(mm)	(in.)	(mm)			
Two- and Four-Way Adhesive Mounting Base										
TC5347A	TC347A	SRA* Adhesive	0.30	1.13	28.58	1.13	28.58	Nylon 6.6	100	1,000
TC5347AX	-							Weatherable Nylon	-	
-	TC347	TC2PA Screws						Nylon 6.6		
-	TC347FR							Flame-Retardant		
-	TC347X							Weatherable Nylon	-	
-	TC347							Radiation Resistant Fluoropolymer	1,000	